

DESCRIPTION

The Trace-lite TL110EX Series is an architectural, full cutoff wallpack that is ideal for parking areas, entrances, walkways, underpasses, loading docks, and recreation areas.

SPECIFICATIONS

Construction:

The Trace-lite TL110EX Series features a durable, die-cast aluminum enclosure with an architectural bronze powder coated finish. Enclosure is fully sealed and gasketed, and is Wet Location Listed for outdoor use. Enclosure and hardware are corrosion resistant. The TL110EX features an internal, anodized aluminum reflector which provides ideal light distribution, and the lamp(s) are protected by a high-impact, heat resistant tempered glass lens.

Lamps & Ballasts

Pulse Start Metal Halide: Lamp 250 watts, utilizing a mogul base, glazed porcelain socket pulse rated for 4KV with a CWA ballast rated for a minimum operating temperature of -30°C (-22°F).

Installation:

The Trace-lite TL110EX Series is ideal for mounting to any vertical surface and features a hinged design for easy access to internal components. Can be wired to a 4" junction box, or surface mounted using 1/2" NPS conduit entry points. Can be mounted in Up-light configuration in Damp Locations ONLY.

Photocontrol (Accessory: PC):

Optional field-installed photocontrol provides dusk-till-dawn security. Input voltage must be specified to match fixture input voltage.

Listing:

The TL110EX is suitable for wet locations.

Warranty:

Any housing component that fails due to manufacturer's defect is guaranteed for two years from time of shipment. Ballasts, Capacitors, and Igniters are warranted for one year from time of shipment. Warranty does not apply to damages caused by improper installation, abuse, fire or acts of God. Lamp is not covered by manufacturer's warranty.


Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____




WHILE SUPPLIES LAST

SAMPLE PHOTOMETRICS

TL110EX-PSMH-250 Mounted at 10'



DIMENSIONS



Approximate Weight: 16 lbs.

Footcandle Correction

Multiply factors times the footcandle values for changes in lamp type.

Lamps	250W PSMH
Factor	.82

ORDERING INFORMATION

Example: TL110EX-PSMH-250-MT

Series	Lamp Type	Lamp Wattage	Input Voltage	Accessories ¹ (Field Installed)
TL110EX	PSMH = Pulse Start Metal Halide	Pulse Start Metal Halide 250 = 250 Watts	MT = 120/208/240/277VAC	PC1 = 120VAC Photocontrol PC2 = 208-277VAC Photocontrol
Notes				WG110EX = Wire Guard

¹ Order as separate line item