

SPECIFICATIONS

Construction:

The Trace-lite TL801 Series features a heavy duty, die-cast aluminum housing with a paintable textured grey powdercoated finish. The cast aluminum guard screws on to the housing and is secured with a headless set screw. The TL801 is suitable for wet locations and complies with UL Standard 1598 for non-hazardous locations. The lamp is protected by a heat and impact resistant clear glass globe that is standard, a frosted glass globe can be specified.

Electronics:

The TL801 utilizes a porcelain medium base socket rated for 600VAC 660W with 8" high temperature wire leads. Two housing sizes are available, a maximum 200 watt unit and a maximum 300 watt unit.

Installation:

The TL801 is available in wall mount and ceiling mount. A weatherproof junction box with 3/4" NPT hubs and rugged mounting tabs is included with wall & ceiling styles and includes one (1) 3/4" x 1/2" reducing bushing for those applications that require 1/2" conduit or fittings.

Listing:

The TL801 is suitable for wet locations and complies with UL standard 1598 for non-hazardous locations where the luminaire must provide protection for the lamp, socket, and wiring from water, corrosive fumes, non-combustible dusts, non-explosive vapors & gases.

Warranty:

Any housing component that fails due to manufacturer's defect is guaranteed for two years from time of shipment. Warranty does not apply to damages caused by improper installation, abuse, fire or acts of God. Lamp is not covered by manufacturer's warranty.

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____



TL801-1B

TL801-1W

LAMP NOT INCLUDED



DIMENSIONS

Mounting	Watts	Width	Height *	Depth
CEILING	200	4 1/4"	9 3/8"	4 1/4"
WALL	200	4 1/4"	12 1/2"	7 1/8"

* Height of wall mount is from the top edge of the wall plate to the bottom of the guard.

ORDERING INFORMATION

Example: TL801-INC-200-2B

Series	Lamp Type	Lamp Wattage	Mounting
TL801	INC = Incandescent	200 = 200 Watt Max	2B ¹ = Ceiling Mount J-Box with 3/4" hubs
			2W ¹ = Wall Mount J-Box with 3/4" hubs
Notes			
¹ 1/2" hub reducer included			

Specifications are subject to change without notice.
Installation must be performed in accordance with
Barron Lighting Group installation instructions.

10810055 02/17