



**ZERO UPLIGHT
LED WALLPACK**

 **TRACE**  **LITE**[®]
commercial & industrial lighting

Up to 12,000 Lumens

Compact, Low Profile

Zero Uplight

Type III and IV Distributions

CCT, Finish and Control Options

WLZ


ZERO UPLIGHT LED WALLPACK

The WLZ Series features an architecturally relevant low profile LED design in lumen packages ranging from 1500 lumens to over 12,000 lumens. Its high efficiency light engine is designed for optimal light control and distribution with zero uplight. This family of product is offered in several size housings to complement any building exterior and accommodates mounting heights up to 35'.

Key Features

- Sleek die-cast aluminum housing with stainless steel hardware and powder coat black, bronze, silver or white finish
- Zero uplight design to minimize light pollution
- 15 to 100 Watt models replace up to 400 Watt HID for up to 70% energy savings
- Efficacies up to 123 LPW at 5000K to maximize utility rebates
- Type III and Type IV distributions for optimal light distribution
- Available in 3000K, 4000K and 5000K CCT
- 0-10V Dimming driver (120-277VAC only)
- Back box is complete with three 1/2" hubs and internal bubble level for easy installation (WLZ1 and WLZ2 - two 1/2" hubs)
- cULus Listed for Wet Locations
- DesignLights Consortium® (DLC) Qualified (verify QPL for specific models)
- Suitable for downlight installation only
- Five year warranty (terms and conditions apply)

Dimensions



Model	A	B	C	D
WLZ1	6.7"	5.0"	5.6"	3.2"
WLZ2	8.0"	5.7"	6.0"	3.2"
WLZ4	10.2"	6.8"	7.8"	5.0"
WLZ7	11.6"	8.3"	9.4"	5.0"
WLZ10	11.6"	10.3"	11.5"	5.0"

Ordering Information (Example: WLZ2-3-4K-BR)

Series/Configuration	Distribution	Input Voltage	CCT	Finish	Options
WLZ1 = 15W, Extra-Small	3 = Type III	BLANK = 120-277VAC	3K = 3000K	BL = Black	DD ⁴ = Dual driver
WLZ2 = 25W, Small	4 ² = Type IV	HVS ³ = 347/480VAC	4K = 4000K	BR = Bronze	PC = 120/277VAC Button photocontrol
WLZ4 = 40W, Medium			5K = 5000K	SV = Silver	SP = 120/277VAC Surge protection
WLZ7 ¹ = 70W, Large				WH = White	SPH = 347/480VAC Surge protection
WLZ10 = 100W, Extra-Large					

Notes

¹ Standard with two drivers

² Not available for WLZ1 configuration

³ Available for WLZ4, WLZ7 and WLZ10 only. Compatible with SPH option only.

⁴ Dual driver option available for WLZ4 and WLZ10 only. Not compatible with photocontrol option, consult factory.

⁵ Order as a separate line item. Shipped in separate box for final installation in the field.

Accessories⁵ (Field Installed)

PCU = 120/277VAC Button photocontrol accessory

Please visit our website for the latest information.

MKT-LIT-WLZ 10840262 04/18



Specs At A Glance*					
Model	WLZ1	WLZ2	WLZ4	WLZ7	WLZ10
Wattage (nominal)	15W	25W	40W	70W	100W
Lumens (lm)	1745	3198	5021	8729	12,393
Efficacy (LPW)	115	118	123	120	116
Equivalency (HID)	50W	100W	150W	250W	400W
Distribution	Type III, IV (WLZ1 Type III only)				
CCT	3000K, 4000K, 5000K				
CRI	≥70				
Input Voltage	120 - 277VAC, 50/60Hz, 347/480V option				
Operating Temp	-40°C to 40°C (-40°F to 104°F)				
Certifications	UL Listed for Wet Locations, DLC				
Warranty	5 Years				
Weight	2.6 lbs	3.3 lbs	6.0 lbs	9.9 lbs	12.1 lbs

* Nominal Wattage, Tested at 5000K CCT, Type III distribution. Values at 120/277VAC. See performance table for more detailed lumen information.

BARRON
lighting group
800.533.3948 • www.barronltg.com