

Unique "Light Bar" design combines LED exit illumination with reliable, low-profile LED emergency lighting. The Revolution series offers maintenance-free, long life dependable service, and easily mounts above doors and in restricted spaces to fit any application.

Model: \_\_\_\_\_ Date: \_\_\_\_\_  
 Accessories: \_\_\_\_\_  
 Job Name: \_\_\_\_\_ Type: \_\_\_\_\_

**FEATURES**

- Unique, adjustable "Light Bar" emergency lighting with ultra-bright, energy efficient white LEDs
- Compact, low profile design
- Easy to install, snap together design
- Rugged, injection-molded UL94 5VA flame retardant, high-temperature thermoplastic housing
- Remote capable standard - up to 2 MLED remote heads
- Universal style - includes 2 face plates, a back plate and mounting canopy
- Charge rate/power "ON" LED indicator light with test button
- Low voltage disconnect eliminates deep discharge
- Brown-out, short circuit and voltage surge protection
- Overcharge protection
- Maintenance-free NiCad battery
- Ceiling, wall or end mount
- UL listed 90 minute emergency run time, 24 hour recharge time
- Constant, uniform illumination by long-life, high intensity, red or green LEDs
- Fully-illuminated 6" characters with 3/4" stroke
- Optional Guardian Self-Test/Self-Diagnostics (G2) available
- Field selectable directional chevrons included for all configurations
- 120/277V dual primary, 60Hz input
- Standard finishes: Black or White
- Suitable for damp location



**WARRANTY**

Any component that fails due to manufacturers defect is guaranteed for 5 years with a separate 5 year pro-rated warranty on the battery. The warranty does not cover physical damage, abuse or acts of God. See the full Exitronix warranty document for detailed information.

**ORDERING INFORMATION Example: CLED-U-WH-G2**

Series	Style	Finish	Options (Factory Installed)	Accessories <sup>2</sup> (Field Installed)
CLED = Red	1 = Single Face	BL = Black	G2 = Self-Test/Self-Diagnostics	WG-1 = Wire Guard (Back Mount)
GCLED = Green	U <sup>1</sup> = Universal	WH = White		WG-2 = Wire Guard (End Mount)
				WG-3 = Wire Guard (Ceiling Mount)
				XG-6 = Poly Guard (Back Mount)

**Notes**

<sup>1</sup> Universal includes 2nd exit face and backplate

<sup>2</sup> Order as separate line item