

RDG-R RECESSED ADJUSTABLE GIMBAL RING

- Constructed of durable lightweight aluminum
- Mounting plate allows fast, easy installation in suspended T-grid or drywall ceilings
- Adjustable, glare-free lighting head

Part No.	Volts	Watts	Lamp Type
RDG-R	6V	8	Halogen

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



L1D THERMOPLASTIC WEDGE BASED SQUARE

- Constructed of impact resistant, UL 5VA thermoplastic
- White or Black with matching mounting plate included
- Add "2" prefix for double head mounting plates

Part No.	Volts	Watts	Lamp Type
L1D	6V	5.4	Tungsten
L2D	6V	7.2	Tungsten
L3D	6V	9	Tungsten
L4D	12V	7.2	Tungsten
L5D	12V	12	Tungsten



L1H THERMOPLASTIC BI-PIN HALOGEN SQUARE

- Constructed of impact resistant, UL 5VA thermoplastic
- White or Black with matching mounting plate included
- 6 volt, 5 watt bi-pin halogen lamps
- Add "2" prefix for double head mounting plate

Part No.	Volts	Watts	Lamp Type
L1H	6V	5	Halogen



Z1P-B THERMOPLASTIC WET LOCATION RATED

- Sealed beam PAR 36
- Constructed of Gray polycarbonate
- Lamp heads are fully gasketed
- Add "2" prefix for double head mounting plates

Part No.	Volts	Watts	Lamp Type	Color
Z1P-B	6V	7.2	Tungsten	Gray
Z5P-B	12V	12	Tungsten	Gray
Z14P-B	6V	9	Tungsten	Black
Z15P-B	12V	12	Tungsten	Black

