

The S900RM Exit Series features a slim architectural design suitable for most indoor environments. Attractive and functional, the S900RM is completely self-contained and utilizes reliable, energy-efficient LED technology.

**FEATURES**

- Pivoting design for simple installation in any application, including wall, ceiling or recessed mounting configurations
- Includes surface mounting canopy or recessed mounting canopy
- Extruded aluminum housing with high-grade, optically true, acrylic panel
- Compact, low profile design
- Maintenance-free NiMH battery
- Low energy consumption, only five (5) Watts
- UL 924 Listed 90 minute emergency run time, 24 hour recharge time
- Low voltage disconnect eliminates deep discharge
- Field applicable pictograms
- 120/347VAC dual primary, 60Hz input
- Standard finishes: White, Black or Brushed Aluminum
- Suitable for Damp Locations

**WARRANTY**

Any component that fails due to a manufacturing defect is guaranteed for three (3) years with a separate two (2) year pro-rated warranty on the battery. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Exitronix warranty document for detailed information.

**UNIVERSAL PICTOGRAMS**

The S900RM provides two (2) pictograms with no directional indicators, a pictogram with a left facing directional indicator and a pictogram with a right facing directional indicator, as well as a one (1) blank panel.

Model: \_\_\_\_\_ Date: \_\_\_\_\_  
 Accessories: \_\_\_\_\_  
 Job Name: \_\_\_\_\_ Type: \_\_\_\_\_




Arrow Left (1pc)



Arrow Right (1pc)



Without Arrow (2pcs)



Blank (1pc)

**ORDERING INFORMATION** Example: S900RM-WB-U-BA

Series	Power Source	Mounting	Finish
S900RM = Universal	WB = With Battery	U = Universal	WH = White
		R = Recessed	BA = Brushed Aluminum
			BL = Black

## CONSTRUCTION

### Housing

Available in Brushed Aluminum, Black or White finish.

### Surface and Recessed Mounting

Engineering grade aluminum extrusion with mounting canopy.

Extruded aluminum housing supplied with galvanized steel adjustable bar hanger assembly.

### Panels

Constructed of acrylic. Stencil letters are 6" high with 3/4" stroke.

### ILLUMINATION

Illumination of the S900RM is achieved with high output, long-lasting white LEDs. The stenciled pictogram legend diffuses light and eliminates hot spots, providing optimal light output.

### ELECTRICAL

#### Input

Dual-voltage input 120 or 347VAC at 60Hz.

#### Nickel Metal Hydride Battery - NiMH (With Battery Only)

Exitronix NiMH batteries are maintenance-free with a life expectancy of 15 years. NiMH batteries perform optimally in temperatures ranging from 32°F to 104°F (0°C to 40°C).

#### Low Voltage Disconnect

Low Voltage Disconnect (LVD) measures the battery terminal voltage. The LVD continuously monitors the battery terminal voltage and if it should fall below a preset voltage threshold, the LVD will disconnect the load. When the battery is recharging and voltage is raised above another preset voltage threshold, the load is automatically reconnected.

#### Test Button

The test button is easy to locate and provides manual verification of the transfer circuit and emergency lamps.

## INSTALLATION

Surface Mounting: Completely universal canopy allows for side wall or ceiling mounting. All hardware is included.

Recessed Mounting: Recessed ceiling mount, accessible above the plenum. Electronics and battery contained in housing. Plug-in battery connector supplied for easy installation. All hardware is included.

### CONFORMANCE TO CODES AND STANDARDS

The S900RM Series is CSA Listed and meets or exceeds the following: NEC requirements and NFPA 101.

### DIMENSIONS

