

The Exitronix Triton series remote is ideal for applications where low-profile, architectural emergency egress lighting is required. Contemporary design and durable die-cast aluminum construction provide attractive, reliable remote lighting that blends seamlessly into any exterior or interior design. Perfect for damp, wet, or cold environments.

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____

FEATURES

- Contemporary, low-profile, streamlined design
- Die-cast aluminum housing
- Remote unit can be run from any 6 volt, emergency lighting unit with a minimum of 12 watts remote power
- External LED status indicator and test button
- Mirrored reflector for enhanced light output
- UL94-5VA flame retardant polycarbonate components
- UV stabilized, vandal resistant, polycarbonate lens
- Suitable for wet or damp location
- A 1/2 inch NPT threaded conduit opening is provided at the top of the enclosure and sealed with a closure plug
- Quick connect mounting back plate
- Standard finishes: Black, White or Bronze



WARRANTY

Any component that fails due to manufacturers defect is guaranteed for 3 years. The warranty does not cover physical damage, abuse or acts of God. See the full Exitronix warranty document for detailed information.

Available While Supplies Last



ORDERING INFORMATION Example: TR-RM-BR

Series	Style	Finish
TR = Triton	RM ¹ = Remote Unit Only	WH = White
		BR = Dark Bronze

Notes

¹ Does not include battery or charging circuit, requires separate 6 volt power supply. Not available with any other options.

REMOTE OPERATION

The Triton remote can be run off any standard emergency lighting unit supplying 6 volts and at least 12 watts of remote power.

Note: Triton emergency lights are not equipped to run remote units.

CONSTRUCTION

Decorative, low-profile, architectural design with die-cast aluminum housing with durable powder coat finishes in white, black and dark bronze. Housing can be paint matched in the field to match any exterior surface. The Triton Series features a fully sealed and gasketed enclosure for Damp and Wet Location applications. Two rigid conduit entry points and a universal J-box mounting pattern make installation quick and easy.

ILLUMINATION

Units come standard with two 6 volt, 6 watt Xenon lamps. Features a mirror-bright reflector and prismatic polycarbonate refractor for ideal light output.

CODE COMPLIANCE

The Triton Series meets or exceeds all performance standards as required by UL 924, NFPA 70, NFPA 101, NEC 700.16 and OSHA.

DIMENSIONS

