

Attractive and easy to install. The VEXC-8 offers energy-efficient LED illumination and reliable emergency lighting in a durable steel enclosure. The VEXC-8 is ideal for any commercial, institutional, or industrial application.

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____

FEATURES

- Meets City of New York Emergency Code requirements
- Enclosure constructed of 22 gauge welded steel
- Universal style – includes 2 face plates, a back plate and mounting canopy
- Charge rate/power "ON" LED indicator light with test button
- Low voltage disconnect eliminates deep discharge
- Brown-out, short circuit and voltage surge protection
- UL recognized maintenance-free lead calcium battery
- Universal Mounting – Ceiling, wall or end mount
- ETL listed 90 minute emergency run time, 24 hour recharge time
- Constant, uniform illumination by long-life, high intensity, red LEDs
- Fully-illuminated 8" characters with 1" stroke
- Optional time delay feature available
- Chevron-style, universal arrow knockouts
- 120/277V dual primary, 60Hz input
- Standard finishes: Black and white



WARRANTY

Any component that fails due to manufacturer's defect is guaranteed for 5 years with a separate 5 year pro-rated warranty on the battery. The warranty does not cover physical damage, abuse or acts of God. Manufacturer reserves the right to charge for such repairs if deemed necessary.



ORDERING INFORMATION

| Model | Description |
|------------------|--|
| VEXC-8-S-WB-WH | 8" Red Letters, Universal, Steel Enclosure, Lead Calcium Battery, White Finish, (3) 6V 9W Lamps, Includes Mounting Canopy |
| VEXC-8-S-WB-WH-2 | 8" Red Letters, Universal, Steel Enclosure, Lead Calcium Battery, White Finish, (2) 6V 12W Lamps, Includes Mounting Canopy |

CONSTRUCTION

Our steel VEXC-8 exit combo enclosure and mounting canopy are 22 gauge galvanized steel with baked-on, powder coated paint. Face plate is .031 thick steel and has 3/4" black letters with red or green LEDs.

Stencil letters are 8" high with 1" stroke, with minimum of 100 ft viewing distance rating as required by UL924 standard.

ILLUMINATION

Illumination of the VEXC-8 series is accomplished utilizing high-intensity, long-life LEDs exceeding UL 924 requirements for brightness and uniformity. LEDs provide excellent illumination while maximizing energy efficiency. LEDs are a maintenance-free solution, providing up to 100,000 hours of use without failure.

EMERGENCY LIGHTS

The VEXC-8 Combo Lamp heads are constructed of high impact thermoplastic in a color matching the finish of the cabinet (white is standard). Heads feature a unique twist locking collar that securely holds the lens and facilitates quick and easy re-lamping. Offered with either (2) 6 volt, 12 watt Par 36 heads or (3) 6 volt, 9 watt Par 36 heads.

ELECTRICAL

Input

Dual-voltage input 120 or 277VAC @ 60Hz.

Sealed Nickel Cadmium Battery – NiCad (With Battery Only)

Exitronix sealed nickel cadmium batteries are maintenance-free with a life expectancy of 15 years. Nickel cadmium batteries offer high discharge rates and continue to perform in a vast temperature range from 0-40 degrees C. NiCad technology provides long lasting, safe and reliable performance by utilizing the jelly-roll design and allows a Ni-Cad cell to deliver a much higher maximum current than an equivalent size alternative battery. As a relatively larger area of the electrode is in contact with the active material in each cell, the internal resistance for an equivalent sized NiCad cell is lower which increases the maximum current that can be delivered.

Emergency

The VEXC-8 Combo series exit will operate for a minimum of 90 minutes during a loss of power with a 24 hour maximum recharge time for the battery.

Brownout Circuit

The brownout circuit monitors the flow of AC current to the unit and triggers the emergency lighting system once a set reduction of AC power occurs. This dip in the voltage will cause many fixtures to extinguish causing loss of normal lighting even though a total power failure has not occurred.

Low Voltage Disconnect

When the battery's terminal voltage falls below predetermined levels, the low-voltage circuit disconnects the emergency lighting load. The disconnect remains in effect until normal power is restored, preventing deep battery discharge and improving the life of the battery. The disconnect will also automatically reconnect the load circuit once the battery voltage returns to a normal value after charging.

Solid-State Transfer

The unit features a solid-state switching transistor which eliminates damaged contacts or mechanical failures associated with relays. The switching circuit is designed to detect a loss of AC power and automatically energizes the lamps. Upon restoration of the AC voltage, the emergency lamps will switch off and the charger will automatically recharge the battery.

Overload and Short-Circuit Protection

The solid-state overload monitoring system in the DC circuit disconnects the lamp load from the battery should excessive wattage demands be made and automatically resets when the overload or short-circuit is removed. This overload current protective characteristic eliminates the need for fuses or circuit breakers for the DC load.

Test Button

Our easily located test button allows for manual verification of proper operation of the transfer circuit and emergency lamps.

INSTALLATION

Interchangeable stencil face and/or back plate slide-fit flush into frame for optimum light seal. Fastening is done by means of a Phillips head screw located in the center bottom frame. Back plate is supplied with a universal knockout pattern for quick, easy installation. Canopy is low profile and offers simple installation for either top or side mount.

CONFORMANCE TO CODES & STANDARDS

The VEXC-8 Combo Series is ETL listed and meets or exceeds the following: UL 924, NEC requirements and NFPA 101.

DIMENSIONS

