



EXTRONIX
emergency lighting

barrontg.com



SUITABLE FOR CITY OF CHICAGO

CHIC Series Steel LED Combo | CHIM Series LED Emergency Lighting Unit
CHIX Series Steel LED Exit | CHIR Series Steel LED Remote Lamps

Low-profile and compact, constructed of rugged 20 gauge steel.


Heat-tempered, impact-resistant translucent glass panels.

UL 924 Listed for Damp Locations.

Universal input voltage from 120VAC to 277VAC, 50/60Hz.

Long life LED lamp heads.

Maintenance free LiFePO4 batteries.



FEATURES & BENEFITS - **CHIC SERIES**

- Two 2.85W LED lamp heads provide 396 lumens each
- Standard with single-face CHIAXC-PANEL-3 (no arrows)
- Ceiling, end or wall mounting (canopy included)
- Maintenance-free LiFePO4 battery
- Up to 62' on-center egress path spacing

ORDERING INFORMATION (Example: CHIC)

Series	Single-face Panel Accessories ^{2,3,4}	Double-face Panel Accessories ^{2,3,5}
CHIC ¹	CHIAXC-PANEL-3 = EXIT (include with fixture) CHIAXC-PANEL-6 = EXIT▶ CHIAXC-PANEL-9 = ◀EXIT CHIAXC-PANEL-12 = ◀EXIT▶	CHIAXC-PANEL-18 = EXIT CHIAXC-PANEL-21 = ◀EXIT, EXIT▶ CHIAXC-PANEL-24 = ◀EXIT▶ CHIAXC-PANEL-17 = STAIRS CHIAXC-PANEL-20 = ◀STAIRS, STAIRS▶
Notes	CHIAXC-PANEL-2 = STAIRS CHIAXC-PANEL-5 = STAIRS▶ CHIAXC-PANEL-8 = ◀STAIRS	
¹ Comes standard with single face CHIAXC-PANEL-3 (no arrows)		
² All panels supplied with red letters on a white background		
³ Order as separate line item, field installed		
⁴ One faceplate only		
⁵ Two faceplates		



FEATURES & BENEFITS - **CHIX SERIES**

- Maintenance-free LiFePO4 battery
- Standard with single-face CHIAXC-PANEL-3 (no arrows)
- Ceiling, end or wall mounting (canopy included)
- Optional remote capacity

ORDERING INFORMATION (Example: CHIX-WB-RC)

Series	Power Source	Options	Single-face Panel Accessories ^{3,4,5}	Double-face Panel Accessories ^{3,4,6}
CHIX ¹	LB = AC Only WB = With Battery	RC ² = Remote Capacity	CHIAXC-PANEL-3 = EXIT (include with fixture) CHIAXC-PANEL-6 = EXIT▶ CHIAXC-PANEL-9 = ◀EXIT CHIAXC-PANEL-12 = ◀EXIT▶ CHIAXC-PANEL-2 = STAIRS CHIAXC-PANEL-5 = STAIRS▶ CHIAXC-PANEL-8 = ◀STAIRS	CHIAXC-PANEL-18 = EXIT CHIAXC-PANEL-21 = ◀EXIT, EXIT▶ CHIAXC-PANEL-24 = ◀EXIT▶ CHIAXC-PANEL-17 = STAIRS CHIAXC-PANEL-20 = ◀STAIRS, STAIRS▶
Notes				
¹ Comes standard with single-face CHIAXC-PANEL-3 (no arrows)				
² WB Only; Compatible with CHIR Indoor Remote or RL1 Outdoor Remote				
³ All panels supplied with red letters on a white background				
⁴ Order as separate line item, field installed				
⁵ One faceplate only				
⁶ Two faceplates				



FEATURES & BENEFITS - **CHIM SERIES**

- Two 2.85W LED lamp heads provide 396 lumens each
- Maintenance-free LiFePO4 battery
- Wall mounted, conduit entry on side and top provided
- Up to 62' on-center egress path spacing
- Optional remote capacity

ORDERING INFORMATION (Example: CHIM-RC)

Series	Options (Factory Installed)	Notes
CHIM = City of Chicago Steel LED Emergency Unit, White Finish	RC ¹ = Remote Capacity, 3W	¹ Compatible with CHIR Indoor Remote or RL1 Outdoor Remote



FEATURES & BENEFITS - **CHIR SERIES**

- Compatible with CHIX and CHIM series
- Lamps include fully adjustable flex arm
- Up to 40' on-center spacing
- Mounts directly to J-box, suitable for surface ceiling or wall mount installations

ORDERING INFORMATION (Example: CHIR-S-WH)

Series ¹	Style	Finish
CHIR = City of Chicago Indoor Remote	S = Single Lamp Head D = Double Lamp Head	WH = White

Notes

¹ Compatible with CHIX and CHIM series, consult factory for compatibility with other product series



Specifications are subject to change without notice.
Installation must be performed in accordance with
Barron Lighting Group installation instructions.

10840443 Rev 1



7885 North Glen Harbor Blvd
Glendale, Arizona 85307
800.533.3948
barronltg.com