

The all new Exitronix Tempo Pro family of LED emergency exit luminaires provide a more complete, compact, powerful light offering with a higher performance than most currently on the market.

Model: \_\_\_\_\_ Date: \_\_\_\_\_  
 Accessories: \_\_\_\_\_  
 Job Name: \_\_\_\_\_ Type: \_\_\_\_\_

### FEATURES

- 3.6 volt compatible
- 4.5" diameter round mounting plate for 3" or 4" standard hole pattern
- Lamp and mounting plate combination is approximately 2" deep
- SMD 1W or 2W LED per lamp head
- Narrow or wide distributions available
- Fully adjustable
- Standard finish: Black or White
- UL 924 and cUL Certified
- Suitable for damp locations



### WARRANTY

Any component that fails due to manufacturers defect is guaranteed for 3 years. The warranty does not cover physical damage, abuse or acts of God. See the full Exitronix warranty document for detailed information. (Terms and conditions apply)

### ORDERING INFORMATION Example: RL52-WH

Series	Finish	Distribution	LED Lamp
RL52 = Single	BL = Black	[BLANK] = Narrow	[BLANK] = 2W LED Lamp
2RL52 = Double	WH = White	W <sup>1</sup> = Wide	LO <sup>1</sup> = 1W LED Lamp

### Notes

<sup>1</sup> Requires longer lead time, consult factory

### COMPATIBLE FIXTURES

Series (Click to view)	Voltage	Remote Capability Max. Wattage	RL52	RL52-LO	2RL52	2RL52-LO
			3.6VDC 2W	3.6VDC 1W	3.6VDC 4W	3.6VDC 2W
<a href="#">LED-51/52 (G3)</a>	3.6V	2W	1	2	n/a	1
<a href="#">LED-90L-G3</a>	3.6V	3W	1	3	n/a	1
<a href="#">S900C (G3)</a>	3.6V	3W	1	3	n/a	1
<a href="#">TPXC-G3</a>	3.6V	1.5W	n/a	1	n/a	n/a
<a href="#">VEX-WPCR</a>	3.6V	1W	n/a	1	n/a	n/a
<a href="#">VLEDC</a>	3.6V	4W	2	4	1	2
<a href="#">VLED-EL90L-G3</a>	3.6V	1.5W	n/a	1	n/a	n/a
<a href="#">WPXC-G3</a>	3.6V	1.5W	n/a	1	n/a	n/a

**ON-CENTER SPACING** (Using multiple units mounted at a typical 7.5 foot height, 85/50/20 reflectance)

Model	# of LED Lamps	3' Path, 6' Corridor	6' Path, 6' Corridor
2RL52-LO	2	10'	9'
2RL52-W-LO	2	18'	14'
2RL52-W	2	25'	21'
2RL52	2	18'	17'

