

DESCRIPTION

6" Sloped ceiling gimbal trim with integrated LED light engine is designed to fit most standard 6" sloped recessed housings, ideal for retrofit new construction applications.

SPECIFICATIONS

Construction:

- Durable aluminum construction with a thermoplastic trim
- E26 Medium screw-base Edison connector provides easy retrofit of incandescent housings
- Gimbal allows for 42° tilt

Optics/ LEDs:

- Long-life LEDs with up to 50,000 hours at 70% lumen maintenance
- Choice of 2700K (±145), 3500K (±245), or 4000K (±275) color temperature with 80 CRI
- Produces 975 lumens (2700K) and 1050 lumens (3500K & 4000K)
- Uses high-power, high-quality LEDs

Electrical:

- LED driver dimmable down to 10% with most dimmers (Lutron Maestro C-L MACL-153MR, Lutron Skylark C-L SCL-153P, Leviton Sureslide Cat. No.6674, Lutron PD-6WCL, Legrand Harmony HCL453PTCCCV6)
- Saves 75% compared to incandescent sources
- Power factor ≥ 0.90
- 120V, 50/60Hz
- 13 Watts power consumption
- Operating temperatures: -20°C to 40°C (-4°F to 104°F)

Installation:

- Designed to fit into 6" ceilings
- Compatible with non-insulated and sloped ceiling
- Easy installation with adjustable torsion spring
- Torsion spring is designed to fit into 6" housing automatically without changing mounting tab
- Tool-less installation

Testing & Compliance:

- Tested in accordance with IESNA LM79 & LM80
- cETLus Listed for Damp Locations
- Energy Star Qualified
- Passes FCC Class B

Warranty:

- Five year warranty (terms and conditions apply)

Note: Environment and application will affect actual performance. Typical values and 25°C used for testing. Specifications subject to change without notice.

Ordering Information

SKUs	Description
BRK-LED56-SGR-27K-ECO	6" LED Sloped Ceiling Gimbal Trim, 2700K CCT
BRK-LED56-SGR-35K-ECO	6" LED Sloped Ceiling Gimbal Trim, 3500K CCT
BRK-LED56-SGR-4K-ECO	6" LED Sloped Ceiling Gimbal Trim, 4000K CCT

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____



Dimensions

