

JLED Series lamp heads feature the efficiency and reliability of LED illumination with durable, thermoplastic housings suitable for wall or ceiling mount.

FEATURES & BENEFITS

- 3.6VDC input
- Available in 0.75W, 1W and 1.5W configurations
- Rugged, injection-molded ABS, 5VA flame retardant, high-temperature thermoplastic housing
- Single and double head configurations available
- cULus listed for Damp Locations
- For use with standard 4" j-box (provided by others)
- Standard finishes: Black or White

WARRANTY

Any component that fails due to a manufacturing defect is guaranteed for three years. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Exitronix warranty document for detailed information. (Terms and Conditions apply)

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



ORDERING INFORMATION Example: JLED1-WH-HO

Series	Finish	LED Lamps
JLED1 = Single Remote Lamp	BL = Black	[BLANK] = 1W LED lamp
JLED2 = Double Remote Lamp	WH = White	HO = 1.5W LED Lamp
		LO ¹ = 0.75W LED lamp

Notes

¹ Requires longer lead time, consult factory

COMPATIBLE FIXTURES

Series (Click to view)	Voltage	Remote Capability Max. Wattage	JLED1	JLED1-LO	JLED1-HO	JLED2	JLED2-LO	JLED2-HO
			3.6VDC 1W	3.6VDC 0.75W	3.6VDC 1.5W	3.6VDC 2W	3.6VDC 1.5W	3.6VDC 3W
LED-51/52 (G3)	3.6V	2W	2	2	1	1	1	n/a
LED-90L-G3	3.6V	3W	3	4	2	1	2	1
S900C (G3)	3.6V	3W	3	4	2	1	2	1
TPXC-G3	3.6V	1.5W	1	2	1	n/a	1	n/a
VLED-EL90L-G3	3.6V	1.5W	1	2	1	n/a	1	n/a
WPXC-G3	3.6V	1.5W	1	2	1	n/a	1	n/a

ON-CENTER SPACING (Using multiple units mounted at a typical 7.5 foot height, 85/50/20 reflectance)

Model	# of LED Lamps	3' Path, 6' Corridor	6' Path, 6' Corridor
JLED2-HO	2	29'	28'
JLED2-LO	2	25'	25'
JLED2	2	23'	25'

