

DESCRIPTION

The LE-SW4 is a Bluetooth enabled, line voltage wall switch used to manage luminaires. The switch can be linked to one or more luminaires or groups of luminaires via the LiteLogic app. The LE-SW4 can initiate up to 4 scenes at the touch of a button. It can be used to easily retrofit existing wall switches.

FEATURES & BENEFITS

- Includes LiteLogic wireless Bluetooth® mesh technology
- Easy on/off and dimming control with up to four (4) scene options
- Ideal for retrofit applications, 120-277VAC (neutral wire required)
- Status indicator light

SPECIFICATIONS

Electrical:

- Input Voltage: 120-277VAC
- Frequency: 50/60Hz
- Input Power: 0.07W

Bluetooth:

- Transmit Range: 100' max
- Radio Frequency: 2.4GHz ± 75MHz
- Bluetooth Version: 5.0

Construction:

- Housing: UL 94-5VA
- IP Rating: IP20, Indoor Use Only
- Finish: White
- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- Storage Temperature: -30°C to 85°C (-22°F to 185°F)


Testing & Compliance:


• cULus Listed, complies to UL 244A, UL 1376, RohS (UL model: WP1017S)

Warranty:

• Five year warranty (terms and conditions apply)

Dimensions





ORDERING INFORMATION (Example: LE-SW4)

Model	Description
LE-SW4	Bluetooth 120-277VAC Wall Switch, 7 Button, White Finish, Neutral Wire Required

Page 1 of 1

Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.



















Scene Controller