



IMPORTANT SAFEGUARDS READ AND FOLLOW ALL SAFETY INSTRUCTIONS.

When using electrical equipment, basic safety precautions should always be followed including the following:

- DISCONNECT AC POWER SUPPLY BEFORE SERVICING.
- Installation and servicing of this equipment should be performed by qualified service personnel only.
- Ensure that the electrical wiring conforms to the National Electrical Code NEC® and local regulations if applicable.
- · Do not mount near gas or electrical heaters.
- Equipment should be mounted in locations and at heights where it will not be readily subjected to tampering by unauthorized personnel.
- The use of accessory equipment not recommended by the manufacturer may cause an unsafe condition.
- · Any modification or use of non-original components will void the warranty and product liability.
- Do not use this equipment for other than intended use.

SAVE THESE INSTRUCTIONS!

Technical Support ■ (623) 580-8943 ■ technical support@barronltg.com







Wiring (Fig. 1)

- 1. Remove current wall plate mounting screws.
- Carefully remove the switch from the switch box. DO NOT disconnect the wires.
- 3. There are three wiring connections on the switch, these are marked HOT, NEUTRAL and GROUND.
- 4. Disconnect the wires from the existing switch.
- 5. Connect the green wire to the GROUND terminal.
- 6. Connect the white wire to the terminal marked NEUTRAL.
- 7. Connect the black wire to the terminal marked HOT.
- Check connections to be sure they are tight and no bare conductors are exposed.
- 9. Insert the switch into the outlet box carefully.
- 10. Make sure to attach the switch to the box using the supplied screws.
- 11. Attach the wall plate.
- 12. Restore power to the circuit breaker and test the system.

Installation (Fig. 2)

- 1. Follow the instructions to connect bluetooth wall switch to the lights. (Fig. 1)
- 2. Press buttons (a) and (a) together for over 3 seconds to enter pairing mode or achieve reset function. This switch can be scanned in the next 30 seconds. (Fig. 2)
- 3. In the LiteLogic App "Switch" page, click to add the switch.
- 4. Select the light / light group to be controlled by this switch.
- 5. For detailed operation please refer to LiteLogic App instructions.





NOTE: This Bluetooth device is compatible with LiteLogic lighting control system only.

How to Install LiteLogic App?

Scan QR Code below to download the APP.





How to Control Lights with a Phone?

Scan the QR Code below for APP instructions.



