



**EXTRONIX**  
emergency lighting

[barrontg.com](http://barrontg.com)



SCAN QR CODE  
FOR PRODUCT DETAILS



# HIGH-ABUSE, VANDAL & LIGATURE-RESISTANT LED EXIT SIGN

Durable, high-abuse, ligature-resistant steel construction.

Vandal-resistant hardware included.

Wall mount configurations.

IP65 Rated and Cold Location options.

Optional Self-test/Self-diagnostics.

# HALRE Series

HIGH-ABUSE, VANDAL AND LIGATURE-RESISTANT LED EXIT

The HALRE series features a robust cold rolled or stainless steel enclosure, a polycarbonate lens, and vandal-resistant hardware, ensuring durability in even the toughest applications. It is available in a wall mount configuration, with red or green LEDs. Additional options include self-test/self-diagnostic (G2), an IP65 rating, and a cold location battery (CL). The HALRE series is the perfect solution for providing clear and reliable exit signage in entryways, stairwells, corridors, and other areas within correctional facilities, detention centers, behavioral health centers, public housing, parks, hospitals, or any space requiring a heavy-duty, vandal-resistant EXIT sign.



## FEATURES & BENEFITS

- Durable, high-abuse, vandal-resistant construction
- Angled design ensures anti-ligature functionality
- Vandal-resistant hardware
- Available in wall mount configurations
- IP65 and cold location options



## SPECIFICATIONS

Illumination:	Constant, uniform illumination by long-life, high intensity, red or green LEDs
Housing:	One piece die-formed cold rolled or stainless steel
Input:	120/277V Dual primary, 60Hz input
Battery:	Maintenance-free NiCad battery
Operating Temp:	Std: 50 °F to 113 °F (10 °C to 45 °C) CL: 32 °F to 122 °F (0 °C to 50 °C)
Run Time:	90 Minute emergency run time, 24 hour recharge time
Legend:	Fully-illuminated 6" characters with 3/4" stroke, field selectable directional chevrons included for all configurations, includes red and green diffusers
Mounting:	Wall Mount
Finishes:	Black, White, or Brushed Finish
Options:	Cold Location Rated, Rated IP65 (Option: CL) Self-Test/Self-Diagnostic (Option: G2) Wet Location Rated, Rated IP65 (Option:WL)
Certifications:	Salt spray test: 1,000 hours; Reflectance: 92% IP65 per IEC 60598, meets or exceeds UL 924 and NFPA 101 Standards, meets or exceeds CSA and NRCAN requirements

## ORDERING INFORMATION (Example: HALRE-WB-B-14-R-W-TH-BF-CL-WL-G2)

Series	Power Source	Housing/Door	Gauge Size	Legend Color
HALRE	LB = AC Only	B = Brushed Stainless Steel	12 <sup>1</sup> = 12 Gauge	G = Green Letters
		C = Painted Cold Rolled Steel	14 = 14 Gauge	R = Red Letters
	WB = NiCad Battery	S = Painted Stainless Steel	16 = 16 Gauge	
			18 = 18 Gauge	

  

Fasteners	Finish	Options	Accessories <sup>5</sup> (Field Installed)
TH = Torx Head w/Center Pin	BL <sup>2</sup> = Black Finish	CL <sup>3</sup> = Cold Location (IP65)	TS = Torx Screwdriver
	BF = Brushed Finish	G2 <sup>4</sup> = Self-Test/Self-Diagnostic	
	WH <sup>2</sup> = White Finish	WL = Wet Location (IP65)	

### Notes

- <sup>1</sup> Only available Cold Rolled Steel material
- <sup>2</sup> N/A with brushed housing material
- <sup>3</sup> WL option not available with CL option
- <sup>4</sup> Only available with battery (WB)
- <sup>5</sup> Field installed, order as separate line item

Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.

10840528 Rev 1

**BARRON**  
lighting group

7885 North Glen Harbor Blvd  
Glendale, Arizona 85307  
800.533.3948  
barronlig.com