



NEW YORK APPROVED LED EDGE-LIT EXIT COMBO

Architectural low-profile design in surface mount and recessed configurations.

Fully adjustable 2.5W LED lamps with up to 40' on-center spacing.

Includes single- and double-face panels.

Optional remote capability.



EXITRONIX
emergency lighting

barrontg.com

NY900C SERIES

LED EDGE-LIT COMBO EXIT SIGN

The NY900C Series is New York City Approved and combines the architectural design of an edge-lit exit sign with ultra-low profile, fully adjustable recessed emergency LED lamp heads for a modern, low-profile aesthetic. The S900C Series is designed for easy recessed or surface mount installation in ceilings or walls. Single- and double-face LED exit configurations are included with brushed aluminum, black or white housing finish options. The S900C Series is ideal for offices, classrooms, corridors, lobbies, and other indoor commercial spaces requiring a minimalist aesthetic for emergency lighting combined with an architectural exit sign.



FEATURES & BENEFITS

- Meets City of New York Emergency Code requirements
- Designed for simple installation and maintenance in any surface or recessed application, surface mount canopy or recessed mount hardware included
- Universal - includes single- and double-face panel configurations
- Optional Self-test/Self-diagnostics (G2) available
- On-center spacing of 40' at 9' mounting height (for non-G2 models)
- 90 Minute emergency run time, 24 hour recharge time
- UL 924 Listed for Damp Locations
- Optional remote capability up to 3W, compatible with two [RL1 remote lamps](#) or one [RL52 remote lamp](#)



SPECIFICATIONS

Illumination:	Long-life, high-intensity, red or green LEDs with 2.5W LED lamp heads (non-G2 models)
Housing:	Steel housing with high-grade acrylic panel
Input:	120/277VAC Dual primary, 60Hz
Battery:	Maintenance-free NiMH battery
Operating Temp:	5°C to 40°C (41°F to 104°F)
Run Time:	UL Listed 90 minute emergency run time, 24 hour recharge time
Electrical:	Low voltage disconnect eliminates deep discharge
Legend:	Fully-illuminated 8" characters with 1" stroke and field-selectable directional chevrons
Mounting:	Surface ceiling, surface wall, recessed ceiling and recessed wall mounting.
Finishes:	Brushed Aluminum, Black or White
Options:	G2 - Self-test/Self-diagnostics R - 3W Remote Capable, compatible with two RL1 remote lamps or one RL52 remote lamp
Certifications:	UL 924 Listed, meets or exceeds NEC requirements and NFPA 101, Suitable for Damp Locations. Meets City of New York Emergency Code requirements.
Warranty:	Three years with a separate five year prorated warranty on the battery. See the full Exitronix warranty document for detailed information and product registration instructions.

ORDERING INFORMATION (Example: NY900C-SM-WH-G2)

Series	Mounting	Finish	Options (Factory Installed)
NY900C ¹ = Universal	R = Recessed	AG = Brushed Alum.	G ² = Self-test/Self-diagnostics
	SM = Surface	BL ² = Black	R ⁴ = 3W Remote Capable
Notes		WH ² = White	
¹ Supplied with single- and double-face panel configurations			
² Consult factory for availability			
³ G2 Option uses 1.5W LED lamp heads			
⁴ Compatible with two RL1 remote lamps or one RL52 remote lamp			
⁵ Not UL Listed item			Accessories^{5,6} (Field Installed)
⁶ Order as separate line item			NY900C-R-FP = Red Single Mirror Panel



Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.

10840391 MKT-LIT-NY900C Rev 6

BARRON
lighting group

7885 North Glen Harbor Blvd
Glendale, Arizona 85307
800.533.3948
barronlitg.com