



**EXTRONIX**  
emergency lighting

[barrontg.com](http://barrontg.com)



# LED STEEL EMERGENCY LIGHTING

Compact, rugged 20 gauge steel enclosure.

Fully-adjustable 1.5W LED lamp heads.

Remote capacity of 20W.

Extended run time (up to 8 hours without remotes).

# RS2 Series

## LED STEEL EMERGENCY LIGHTING

The Exitronix RS2 Series combines LED performance and dependability with a rugged 20 gauge steel enclosure. The corrosion-resistant, value-driven emergency unit features fully-adjustable LED lamp heads and easy installation. RS2 features 20W of additional battery capacity for extended run time or powering remote lamps.



### FEATURES & BENEFITS

- High impact, injection molded, thermoplastic LED lamp heads
- 1.5W (12 LEDs x .125 watt) per lamp head
- Enclosure constructed of rugged 20 gauge steel
- Remote capacity of 20W
- Extended run time (up to 8 hours without remotes)
- Compatible with **MLED** LED remote lamps

### SPECIFICATIONS

Illumination:	Two top mounted, fully adjustable, high intensity lamp heads with high performance, chrome plated, metallized reflector and plastic lens
Housing:	Rugged 20 gauge steel with powder coated finish
Input:	120/277VAC Dual primary, 60Hz
Battery:	Maintenance-free sealed lead calcium battery
Operating Temp:	20°C to 50°C (68°F to 122°F)
Run Time:	90 minute emergency run time, 24 hour recharge time
Electrical:	Low voltage disconnect eliminates deep discharge
Mounting:	Shelf mount or universal mounting pattern provided for wall mount; knockouts for top or side conduit entry
Finishes:	Black or White
Certifications:	UL 924 Listed for Damp Locations, Meets NFPA 101 Life Safety Code, NEC, OSHA
Warranty:	Any component that fails due to a manufacturing defect is guaranteed for five years with a separate two year prorated warranty on the battery. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Exitronix warranty document for detailed information and product registration instructions. (Terms and Conditions apply)

### ORDERING INFORMATION (Example: RS2-6-27-WH)

Series	Battery	Wattage	Finish	Accessories <sup>1</sup> (Field Installed)
RS2	6 = 6 Volt Lead Calcium	27 = 27 Watts	BL = Black WH = White	WG-S = Wire Guard (Back Mount) XG-PS = Poly Guard (Back Mount) MLED1-W = Indoor Single Remote White MLED2-W = Indoor Double Remote White MLED1-B = Indoor Single Remote Black MLED2-B = Indoor Double Remote Black MLED1-G-WP = Outdoor Single Remote Gray MLED2-G-WP = Outdoor Double Remote Gray MLED1-B-WP = Outdoor Single Remote Black MLED2-B-WP = Outdoor Double Remote Black

**Notes**  
<sup>1</sup> Order as separate line item



## EQUITY LINE

Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.

10840458 MKT-LIT-RS2

**BARRON**  
lighting group  
7885 North Glen Harbor Blvd  
Glendale, Arizona 85307  
800.533.3948  
barronlitg.com