



EXITRONIX
emergency lighting

barronltg.com



LED STEEL COMPACT EMERGENCY LIGHTING

**Compact, rugged 20 gauge steel enclosure.
Fully-adjustable, PAR18 5W or 7W LED lamp heads.
Available in 6V or 12V with capacities up to 90 watts.
Extended run time or remote capable.
Top or side mounted lamp heads.**

RSL Series

LED STEEL COMPACT EMERGENCY LIGHTING

The Exitronix RSL Series combines LED performance and dependability with a compact, rugged 20 gauge steel enclosure. The corrosion resistant units feature fully adjustable LED lamp heads and easy installation. Most models have additional battery capacity for extended run time or powering remote lamps.



FEATURES & BENEFITS

- PAR18 thermoplastic LED lamp heads
- Enclosure constructed of rugged 20 gauge steel
- Available in 6V or 12V with capacities up to 90 watts
- Knockouts for side mounted heads
- Extended run time or remote capable
- Optional Guardian Self-test/Self-diagnostics (G2) available
- Buy American Act (BAA) compliant
- Compatible with [MIST](#) and [RSMR](#) LED remote lamp heads
- Meets City of New York Emergency Code requirements



SPECIFICATIONS

Illumination:	Two top (standard) or side mounted, long-life, high intensity PAR18 5W or 7W LED lamp heads
Housing:	Rugged 20 gauge steel with powder coated finish
Input:	120/277VAC Dual primary, 60Hz
Battery:	Maintenance-free sealed lead calcium or NiCad battery available
Operating Temp:	10°C to 40°C (50°F to 104°F)
Run Time:	CSA Listed 90 minute emergency run time, 24 hour recharge time
Electrical:	Low voltage disconnect eliminates deep discharge, brownout, short circuit and voltage surge protection
Mounting:	Shelf mount or universal mounting pattern with keyhole slots provided for wall mount
Finishes:	Black or White
Options:	G2 - Self-test/Self-diagnostics
Certifications:	Conforms to UL 924 standards, Meets NFPA 101 Life Safety Code, NEC, OSHA
Warranty:	Any component that fails due to a manufacturing defect is guaranteed for five years with a separate five year prorated warranty on the battery. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Exitronix warranty document for detailed information and product registration instructions. (Terms and Conditions apply)

ORDERING INFORMATION (Example: RSL-6-18-0605-W-G2)

Series	Battery	Wattage ¹		Lamp Heads	Finish	Options (Factory Installed)
RSL	6 = 6 Volt Lead Calcium	6 Volt, Lead Calcium	6 Volt, NiCad	0 = No Lamp Heads	B = Black	G2 = Self-test/Self-diagnostics
	12 = 12 Volt Lead Calcium	18 = 18 Watts	22 = 22 Watts	6 Volt PAR18 LED	W = White	
	6N = 6 Volt NiCad	27 = 27 Watts	42 = 42 Watts	0605 = (2) 5W Heads		
	12N = 12 Volt NiCad	36 = 36 Watts	54 = 54 Watts	12 Volt PAR18 LED	Accessories² (Field Installed)	
		60 = 60 Watts	90 = 90 Watts	1205 = (2) 5W Heads		XG-PS = Poly Guard (Back Mount)
		12 Volt, Lead Calcium	12 Volt, NiCad	1207 = (2) 7W Heads		
		36 = 36 Watts	42 = 42 Watts			
		60 = 60 Watts	90 = 90 Watts			
Notes						
¹ Compatible with the MIST & RSMR LED remote lamp heads						
² Order as separate line item						