


SCS Surface Mount LED Soft Square Canopy

The SCS-S is Trace-Lite's new low-profile 12" surface mount soft square canopy with optional integral factory-installed dimming occupancy sensor with daylight sensing capabilities. This canopy optimizes optical performance and long-life with superior thermal management in an attractive and durable die-formed aluminum enclosure and premium PMMA lens that does not yellow over time.

Key Features

- 12" Square canopy with rounded corners in a precision die-formed aluminum enclosure and non-metallic mounting backplate
- PMMA optics engineered for garage applications, will not yellow over time
- Up to 123LPW to maximize energy savings and utility rebates
- Optional integral occupancy sensor with daylight harvesting capabilities
- UL Listed for Wet Locations

Dimensions



Ordering Information Example: SCS-S-40-LG-VS-4K-WH-SC

23		
		-0
	*	000 000
000		
A SW3		
	All Carlos Concellant	



Specs At A Glance*				
Model	SCS-S-40	SCS-S-54		
Wattage (W)	35	54		
Lumens (Im)	4663	6288		
Efficacy (LPW)	123	119		
Equivalency (HID)	100W	150W		
Distribution	LED Garage (LG) - Type V Square Short			
ССТ	4000K			
CRI	≥72			
Input Voltage	120-277VAC, 50/60Hz, 0-10V Dimmable			
Operating Temp	-40°C to 40°C (-40°F to 104°F)			
Certifications	cETLus Listed, Wet Locations Covered Canopy, DLC PREMIUM			
Warranty	5 Y	'ears		
Weight	8.0 lbs			

*Nominal Wattage

Note: Environment and application will affect actual performance. Typical values and 25°C used for testing. Specifications subject to change without notice.

Series	Wattage	Optics	Input Voltage	ССТ	Finish	Options
SCS-S	40 = 35 Watts	5 Watts LG = LED Garage VS = 120-277V 4K = 40	4K = 4000K	WH = White	SC = Integral dimming sensor with daylight harvesting	
	54 = 54 Watts					

Notes	Accessories ¹ (Field Installed)
¹ Order as separate line item, shipped in separate box	TL-RCSCH = Remote control for SC option



800.533.3948 | barronitg.com

MKT-LIT-SCS 10840301 10/18