



TRACE LITE
commercial & industrial lighting

barronltg.com

LOW-PROFILE ARCHITECTURAL WALLPACK

UL 924 Listed emergency egress models.

Integral motion detection and photocontrol options.

Architectural die-cast aluminum housing.

UL Listed for Wet Locations.

California Title 24 compliant.

SLW Series

LOW-PROFILE, ARCHITECTURAL LED WALLPACK WITH EGRESS OPTION

The slim architectural SLW Series LED wallpack features integral motion detection and photocontrol in both “normally on” and UL 924 Listed emergency egress models. The fully gasketed die-cast enclosure is UL Listed for Wet Locations. The SLW’s 15 Watt LED light engine delivers 1750 lumens in AC mode and 650 lumens in emergency mode. Zero uplight optics reduce light pollution.



FEATURES & BENEFITS

- Architectural die-cast aluminum housing
- Snap-fit housing to mounting plate for easy access and installation
- Universal pattern knockouts for mounting to 3” and 4” J-box
- ½” Threaded conduit entry for top feed
- Available in Bronze, Black, Silver or White finish
- EM option uses long-life, maintenance-free, rechargeable high temperature NiCad battery which includes internal heater suitable for cold locations and draws an additional 17 Watts
- PIR and Photocontrol:
 - Internal switch allows photocontrol to be enabled or disabled
 - Connector can be disconnected to disable PIR
- 15 Watt high-power LED light engine delivers 1500 lumens (600 lumens in emergency mode for 60’ on center spacing)
- Standard 4000K CCT, CRI ≥ 70, L70 > 54,000 hours
- LED array is protected by a high-impact, UV-resistant polycarbonate lens

SPECS AT A GLANCE

| | |
|-----------------------|--|
| Wattage (W)* | 15W (AC) 5W (EM) |
| Lumens (lm) | 1750 (AC) 650 (EM) |
| Efficacy (LPW) | 116 |
| Equivalency | 100W HID |
| CCT | 4000K |
| CRI | ≥ 70 |
| Input Voltage | 120-277VAC, 60Hz |
| Warranty | 5 Years |
| Certifications | UL 924 Listed for Wet Locations, NFPA 101, Title 24, Title 20 |
| Operating Temp | Std: 0°C to 50°C (32°F to 122°F) EM: -25°C to 50°C (-13°F to 122°F) |
| Weight | 3.7 lbs (EM model: 4.5 lbs) |

* Nominal Wattage, tested at 5000K CCT. Values at 120/277VAC.

Note: Environment and application will affect actual performance. Typical values and 25°C (77°F) used for testing. Specifications subject to change without notice.

ORDERING INFORMATION Example: SLW-15-4K-BL-EM (For fixtures with Guardian G3 remote monitoring and reporting, [click here.](#))

| Series | Wattage | CCT | Finish | Options |
|--------------------------------------|----------|------------|------------------|--|
| SLW | 15 = 15W | 4K = 4000K | (Blank) = Bronze | EM ¹ = UL 924 Emergency battery back-up with self-test/ self-diagnostics, cold location |
| | | | BL = Black | |
| | | | SV = Silver | |
| | | | WH = White | |
| Notes | | | | |
| ¹ EM model not DLC Qualified product | | | | |



Specifications are subject to change without notice.
Installation must be performed in accordance with
Barron Lighting Group installation instructions.

10840258 Rev 8



7885 North Glen Harbor Blvd
Glendale, Arizona 85307
800.533.3948
barronlgtg.com