



# LED SOCIAL DISTANCING SIGNS

Available in plastic, die-cast, edge-lit and wet location enclosures

Single or double-faced configurations

Built with the same quality components as our Exit signs



# In today's health-conscious environment, social distancing has become a necessity. Help keep your employees, customers, patients and visitors safe with Social Distancing signage from Exitronix.

Available in a wide variety of enclosures including die-cast aluminum, thermoplastic, attractive edge-lit designs and outdoor configurations, Exitronix Social Distancing signage is perfect for any application.

## FEATURES

- Available in plastic (VEX), die-cast (400E), edge-lit (900E) and wet location (VEX-WP) enclosures
- Single or double-faced configurations
- Built with the same quality components as our Exit signs

## APPLICATIONS

- Hospitals/Clinical Labs
- Radio Stations/Concert Venues
- Stadiums/Gymnasiums
- School Campus
- Retail
- Restaurants/Bars

### VEX-SD Series Thermoplastic

- Compact, low-profile design with easy to install, snap together design
- Rugged, injection-molded UL 94 5VA flame-retardant, high-temperature thermoplastic housing
- Ceiling, end or wall mounted
- Maintenance-free NiCad battery
- 120/277VAC Dual primary, 60Hz input



ORDERING INFORMATION Example: VEX-1-BP-LB-WH-SD01

Series	Style	Housing Type	Power Source	Finish	Legend <sup>2</sup>
VEX = Red	U <sup>1</sup> = Universal	BP = Plastic	LB = AC Only	WH = White	SD01 = 6' Distance
GVEX = Green	1 = Single-Face		WB = With Battery		SD02 = 6' Distance w/Masked Figures
					SD03 = 6' Distance Masks Required

**Notes** <sup>1</sup> Universal includes second exit face and backplate <sup>2</sup> Consult factory for alternate legends and custom configurations

### 400E-SD Series Die-Cast Aluminum

#### Available While Supplies Last

- Specification grade exit sign with an enclosure constructed of precision die-cast aluminum
- Maintenance-free NiCad batteries
- Ceiling, wall or end mount
- 120/277VAC Dual primary, 50/60Hz input



ORDERING INFORMATION Example: 402E-LB-BA-SD01

Series		Power Source	Finish	Legend <sup>1</sup>
402E = Red Single-Face	403E = Red Double-Face	LB = AC Only	BA = Brushed Alum. w/ Alum. Face	SD01 = 6' Distance
G402E = Green Single-Face	G403E = Green Double-Face	WB = NiCad Battery (std.)	BB = Black w/ Black Face	SD02 = 6' Distance w/Masked Figures
B402E = Blue Single-Face	B403E = Blue Double-Face		BL = Black w/ Alum. Face	SD03 = 6' Distance Masks Required
			WW = White w/ White Face	

**Notes** <sup>1</sup> Consult factory for alternate legends and custom configurations



## AVAILABLE LEGENDS

Consult factory for custom applications



## 900E-SD Series Architectural Edge-Lit

- Attractive specification-grade aluminum design
- High-clarity acrylic panels
- Ceiling recessed, wall recessed, surface ceiling, end or wall mount
- 120/277VAC Dual primary, 50/60Hz input
- Maintenance-free NiCad (NC) or Sealed Lead Calcium (WB) batteries



### ORDERING INFORMATION Example: 902E-U-WB-RM-BA-SD01

Series	Mounting	Power Source	Panel Color	Finish	Legend <sup>3</sup>
902E = Single-Face	R = Recessed	LB = AC Only	GC <sup>2</sup> = Green Letters/Clear Panel	BA = Brushed Alum.	SD01 = 6' Distance
903E <sup>1</sup> = Double-Face	U = Universal Surface	NC = NiCad	GM = Green Letters/Mirror Panel	BL = Black	SD02 = 6' Distance w/Masked Figures
	WR <sup>2</sup> = Wall Recessed	WB = With Battery	GW = Green Letters/White Panel	WH = White	SD03 = 6' Distance Masks Required
			RC <sup>2</sup> = Red Letters/Clear Panel		
			RM = Red Letters/Mirror Panel		
			RW = Red Letters/White Panel		
			BC <sup>2</sup> = Blue Letters/Clear Panel		
			BM = Blue Letters/Mirror Panel		
			BW = Blue Letters/White Panel		

**Notes**

<sup>1</sup> Double face available with white or mirror panel only

<sup>2</sup> Single face, clear panels only (RC or GC)

<sup>3</sup> Consult factory for alternate legends and custom configurations

## VEX-WP-SD Series Wet Location

- Ideal for Wet Location applications in extreme conditions
- UV-stabilized, rugged injection-molded, UL 94 5VA flame-retardant, high temperature polycarbonate housing with impact-resistant, polycarbonate shield
- One piece molded weatherproof silicone gasket
- Ideal for cold locations ranging from -20°C to 50°C (-4°F to 122°F)
- Maintenance-free NiCad battery
- Ceiling, wall or end mount
- 120/277VAC Dual primary, 60Hz input



### ORDERING INFORMATION Example: VEX-WP-1-WB-WH-SD01

Series	Style	Power Source	Finish	Legend <sup>3</sup>
GVEX-WP = Green	1 = Single-Face	LB = AC Only	BL = Black	SD01 = 6' Distance
VEX-WP = Red	2 = Double-Face	WB = With Battery	GR = Gray	SD02 = 6' Distance w/Masked Figures
			WH = White	SD03 = 6' Distance Masks Required

**Notes** <sup>1</sup> Consult factory for alternate legends and custom configurations



