

LED LINEAR HIGHBAY
WITH AVAILABLE UPLIGHT

ULHB



4 Sizes

110 · 180 · 260 · 340



3 Wattages

FIELD-SWITCHABLE



4 CCTs

FIELD-SWITCHABLE



3 Lenses

GENERAL · AISLE · WIDE



 **TRACE LITE**[®]
commercial & industrial lighting

15% Uplight Accessory

BRIGHTEST IN THE INDUSTRY

The ULHB Series linear highbay with available uplight offers superior performance and energy-efficiency in a low-profile, compact design. An extremely flexible solution to fit any situation, this series offers field-switchable CCT between 3000K, 3500K, 4000K, and 5000K, and 3 field-switchable power levels in lumen packages up to 60,000 lumens.

- Die-formed steel housing in a white finish
- All configurations are power and CCT switchable
- Rotatable LED panels adjust to 0°, 15°, and 30°
- General 90° distribution, optional aisle lens or wide lens distribution
- Uplight module accessories provide 15% of fixture's wattage in uplight and install easily with no wiring required
- Built in 3.5mm AUX receptacle for easy plug and play sensor installation
- DesignLights Consortium® (DLC) PREMIUM Qualified
- Meets Title 24 requirements for dimming and control of light fixtures

LED LINEAR HIGHBAY WITH AVAILABLE UPLIGHT ULHB



Rotatable LED Panels Adjust to 0°, 15° or 30°



Three Available Lenses; General, Aisle & Wide

Specs at a Glance

| Configuration | ULHB-110 | ULHB-180 | ULHB-260 | ULHB-340 |
|----------------|--|---------------------------|---------------------------|---------------------------|
| Wattage (W)* | 70W-90W-110W Switchable | 140W-160W-180W Switchable | 180W-230W-260W Switchable | 285W-310W-340W Switchable |
| Lumens (lm) | 12000-15000-18000 | 24000-27000-30000 | 32000-40000-48000 | 50000-55000-60000 |
| Efficacy (LPW) | 170 | | | |
| Distribution | General 90°, Optional Aisle Lens Distribution (60° x 90°) or Optional Wide Lens Distribution (110° x 110°) | | | |
| CCT (K) | 3000K-3500K-4000K-5000K Switchable | | | |
| CRI | ≥80 | | | |
| Input Voltage | 120-277VAC, 50/60Hz, 0-10V Dimmable | | | |
| Operating Temp | -20°C to 45°C (-4°F to 113°F) | | | |
| Certifications | UL Listed for Damp Locations, DLC PREMIUM | | | |
| Warranty | 5 Years | | | |
| Weight | 4.1lbs | 5.5lbs | 9.6lbs | 9.6lbs |

* Nominal wattage. Tested at 3000K CCT, 170Lm/W.

Note: Environment and application will affect performance. Typical values and 25°C used for testing. Specifications subject to change without notice.



ORDERING INFORMATION (Example: ULHB-110-G-VS-CP)

| Model | Wattage | Distribution | Input Voltage | CCT | Options (Factory Installed) |
|-------|--------------------|---------------------------------|-----------------|-----------------------------|---------------------------------------|
| ULHB | 110 = 70/90/110W | A = Aisle 60°X90° Distribution | VS = 120-277VAC | CP = CCT & Power Selectable | BB1 = 25W Battery Backup |
| | 180 = 140/160/180W | G = General 90° Distribution | | | BB2 ¹ = 60W Battery Backup |
| | 260 = 180/230/260W | W = Wide 110°x110° Distribution | | | |
| | 340 = 285/310/340W | | | | |

| LiteLogic Accessories ² (Field installed) | LED Accessories ² (Field installed) |
|---|---|
| LE-MS3-AUX-HB1 = Bluetooth Enabled Dimming Occupancy Sensor, PIR | ULHB-110-UM = 2 Uplight Modules for ULHB-110 |
| LE-SW2 = Bluetooth Enabled, 5-Button, Battery Powered Wall Switch | ULHB-180-UM = 2 Uplight Modules for ULHB-180 |
| LE-SW3 = Bluetooth Enabled, 3-Button, Line Voltage Wall Switch (Neutral Required) | ULHB-260-UM = 2 Uplight Modules for ULHB-260 |
| LE-SW4 = Bluetooth Enabled, 7-Button, Line Voltage Wall Switch (Neutral Required) | ULHB-340-UM = 2 Uplight Modules for ULHB-340 |
| LE-WP = Wallplate for LE-SW2, White | |
| TL-MSP12 = Dimming Occupancy Sensor, PIR | Lens Accessories ² (Field installed) |
| TL-MSSW-REMOTE = Remote for SC Dimming Sensor | ULHB-110-AL = Aisle 60°X90° Lens Kit for ULHB-110 |
| | ULHB-180-AL = Aisle 60°X90° Lens Kit for ULHB-180 |
| | ULHB-260/340-AL = Aisle 60°X90° Lens Kit for ULHB-260 & ULHB-340 |
| | ULHB-110-WL = Wide 110°X110° Lens Kit for ULHB-110 |
| | ULHB-180-WL = Wide 110°X110° Lens Kit for ULHB-180 |
| | ULHB-260/340-WL = Wide 110°X110° Lens Kit for ULHB-260 & ULHB-340 |

| Notes | Mounting Accessories ² (Field installed) |
|---|--|
| ¹ Compatible with ULHB-260 & ULHB-340 | ULHB-110/180-SPM = Surface and Pendant Mount Kit for ULHB-110 & ULHB-180 |
| ² Order as a separate line item, shipped in a separate box for installation in the field | ULHB-260/340-SPM = Surface and Pendant Mount Kit for ULHB-260 & ULHB-340 |