



**TRACE LITE**  
commercial & industrial lighting

[barronltg.com](http://barronltg.com)



# ADJUSTABLE LED WALLPACK

Adjust fixture from 0° (pointing down) up to 90°.

Field-switchable power from 1,600 to 11,100 lumens.

Field-switchable CCT 3000K-4000K-5000K.

DesignLights Consortium® (DLC) PREMIUM Qualified.



# WTA-CP Series

## ADJUSTABLE LED WALLPACK

Experience unparalleled versatility with the WTA-CP Series. This compact and energy-efficient adjustable LED wallpack offers lumen packages ranging from 1,600 to 11,100 lumens. Adjustable positioning from 0° to 90° allows you to have full control over your lighting and accounts for varying applications. With power selectability and color selectable options between 3000K, 4000K, and 5000K CCT, plus a built-in photocontrol, you can create the perfect ambiance for any environment. Ideal for retail entrances, schools, medical complexes, commercial buildings, and multifamily properties.



## FEATURES & BENEFITS

- Die-cast aluminum housing in a powder coated bronze finish with stainless steel hardware
- UV-stabilized polycarbonate lens
- Integral heat sink maximizes heat dissipation for longer LED life
- Hinged back box isolates drivers from LEDs and offers easy access to drivers
- Backbox includes three ½" conduit entry points (one on top and two on the sides)
- Built in photocontrol on the top of the unit – simply remove cap to enable
- Less than 1% uplight to minimize light pollutions (pointing down)
- Type III distribution pointing down (3000K – Type II)
- Up to 11,100 lumens for a variety of applications
- Efficacies up to 155 LPW maximize energy savings and utility rebates
- Switchable between 3000K, 4000K and 5000K CCT
- Class 2 power supply, 120 to 277VAC, 50/60Hz
- 0-10V Dimming driver
- Housing can be adjusted from 0° to 90° for forward throw (10° increments)
- Backbox accommodates conduit entry on both sides and top
- Mounts to a standard 3-½" or 4" square electrical J-box
- LiteLogic Bluetooth Enabled Dimming Occupancy Sensor, PIR, Includes 12V Power Adapter, Black Finish ([LE-MS3W-KIT-BL-12V-A-R](#))
- LiteLogic Dimming Occupancy Sensor Kit, PIR ,Includes 12V Power Adapter, Black Finish (SC-MSP12-KIT-BL-12V-A-R)
- cULus Listed for Wet Locations
- DesignLights Consortium® (DLC) PREMIUM Qualified
- Operating temperatures: -40°C to 40°C (-40°F to 104°F)

## ORDERING INFORMATION (Example: WTA-40-VS-CP-BR)

Model	Description
WTA-27-VS-CP-BR	Adjustable LED Wallpack, Power Switchable 11W/16W/22W/27W, 120-277VAC, 0-10V Dimming, Color Switchable 3000K/4000K/5000K CCT, Bronze Finish
WTA-40-VS-CP-BR	Adjustable LED Wallpack, Power Switchable 16W/24W/32W/40W, 120-277VAC, 0-10V Dimming, Color Switchable 3000K/4000K/5000K CCT, Bronze Finish
WTA-80-VS-CP-BR	Adjustable LED Wallpack, Power Switchable 32W/48W/64W/80W, 120-277VAC, 0-10V Dimming, Color Switchable 3000K/4000K/5000K CCT, Bronze Finish

### LiteLogic Accessories<sup>1</sup> (Field Installed)

[LE-MS3W-KIT-BL-12V-A-R](#) = Bluetooth Enabled Dimming Occupancy Sensor, PIR, Includes 12V Power Adapter, Black Finish

SC-MSP12-KIT-BL-12V-A-R = Dimming Occupancy Sensor Kit, PIR ,Includes 12V Power Adapter, Black Finish

TL-MSSW-REMOTE = Remote for Dimming Sensor Accessory (SC-WTA-BL-12V-KIT)

### Notes

<sup>1</sup> Order as a separate line item, shipped in a separate box for installation in the field

## SPECS AT A GLANCE

Model	WTA-CP-27	WTA-CP-40	WTA-CP-80
CCT (K)	3000K-4000K-5000K (Switchable)		
Wattage (W)*	11W-16W-21W-27W (Switchable)	16W-24W-32W-40W (Switchable)	32W-48W-64W-80 (Switchable)
Lumens (lm)	1,600 - 3,700	2,300 - 5,500	4,700 - 11,100
Efficacy (LPW)	Up to 155 Lumens Per Watt		
CRI	≥80		
Input Voltage	120-277VAC, 50/60Hz, 0-10V Dimming		
Operating Temp	-40°C to 40°C (-40°F to 104°F)		
Certifications	UL Listed for Wet Locations, DLC PREMIUM		
Warranty	5 Years		

\* Nominal Wattage, tested at 5000K CCT. Values at 120/277VAC. Note: Environment and application will affect actual performance. Typical values and 25°C (77°F) used for testing. Specifications subject to change without notice.



Specifications are subject to change without notice.  
Installation must be performed in accordance with  
Barron Lighting Group installation instructions.

10840514 Rev 3

**BARRON**  
lighting group  
7885 North Glen Harbor Blvd  
Glendale, Arizona 85307  
800.533.3948  
barronlitg.com