

In today's health-conscious environment, social distancing has become a necessity. Help keep your employees, customers, patients and visitors safe with Social Distancing signage from Exitronix. Available in a wide variety of enclosures including die-cast aluminum, thermoplastic, attractive edge-lit designs and outdoor configurations, Exitronix Social Distancing signage is perfect for any application.

FEATURES

- Available in plastic (VEX), die-cast (400E), steel (700E), edge-lit (900E) and wet location (VEX-WP) enclosures
- Single or double-faced configurations
- Built with the same quality components as our Exit signs

APPLICATIONS

- Hospitals/Clinical Labs
- Radio Stations/Concert Venues
- Stadiums/Gymnasiums
- School Campus
- Retail
- Restaurants/Bars

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____



VEX



400E



900E



700E

AVAILABLE LEGENDS (Consult factory for custom legends)



SD01



SD02



SD03

VEX-SD Series Thermoplastic

- Compact, low-profile design with easy to install, snap together design
- Rugged, injection-molded UL 94 5VA flame-retardant, high-temperature thermoplastic housing
- Ceiling, end or wall mounted
- Maintenance-free NiCad battery
- 120/277VAC Dual primary, 60Hz input



Download [VEX specification](#) for more information

ORDERING INFORMATION Example: VEX-1-BP-LB-WH-SD01

Series	Style	Housing Type	Power Source	Finish	Legend ²
VEX = Red	U ¹ = Universal	BP = Plastic	LB = AC Only	WH = White	SD01 = 6' Distance
GVEX = Green	1 = Single-Face		WB = With Battery		SD02 = 6' Distance w/Masked Figures
					SD03 = 6' Distance Masks Required

Notes ¹ Universal includes second exit face and backplate ² Consult factory for alternate legends and custom configurations

400E-SD Series Die-Cast Aluminum

- Specification grade exit sign with an enclosure constructed of precision die-cast aluminum
- Maintenance-free NiCad batteries
- Ceiling, wall or end mount
- 120/277VAC Dual primary, 50/60Hz input



Download [400E specification](#) for more information

ORDERING INFORMATION Example: 402E-LB-BA-SD01

Series	Power Source	Finish	Legend ¹
402E = Red Single-Face	403E = Red Double-Face	LB = AC Only	BA = Brushed Alum. w/ Alum. Face
G402E = Green Single-Face	G403E = Green Double-Face	WB = NiCad Battery (std.)	BB = Black w/ Black Face
B402E = Blue Single-Face	B403E = Blue Double-Face		BL = Black w/ Alum. Face
			WW = White w/ White Face

Notes ¹ Consult factory for alternate legends and custom configurations

700E-SD Series Steel

- Full enclosure constructed of rugged 20 gauge steel
- Maintenance-free NiCad batteries

- Ceiling, end or wall mount
- 120/277VAC Dual primary, 60Hz input



Download [700E specification](#) for more information

ORDERING INFORMATION Example: 702E-WB-BL-SD01

Series	Power Source	Finish	Legend ¹
702E = Red Single-Face 703E = Red Double-Face	LB = AC Only	BL = Black	SD01 = 6' Distance
G702E = Green Single-Face G703E = Green Double-Face	WB = NiCad Battery (std.)	WH = White	SD02 = 6' Distance w/Masked Figures
B702E = Blue Single-Face B703E = Blue Double-Face			SD03 = 6' Distance Masks Required

Notes ¹ Consult factory for alternate legends and custom configurations

900E-SD Series Architectural Edge-Lit

- Attractive specification-grade aluminum design
- High-clarity acrylic panels
- Ceiling recessed, surface ceiling, end or wall mount

- 120/277VAC Dual primary, 50/60Hz input
- Maintenance-free NiCad (NC) or Sealed Lead Calcium (WB) batteries



Download [900E specification](#) for more information

ORDERING INFORMATION Example: 902E-U-WB-RM-BA-SD01

Series	Mounting	Power Source	Panel Color	Finish	Legend ²
902E = Single-Face	R = Recessed	LB = AC Only	GC = Green Letters/Clear Panel	BA = Brushed Alum.	SD01 = 6' Distance
903E ¹ = Double-Face	U = Universal Surface	NC = NiCad	GM = Green Letters/Mirror Panel	BL = Black	SD02 = 6' Distance w/Masked Figures
		WB = With Battery	GW = Green Letters/White Panel	WH = White	SD03 = 6' Distance Masks Required
			RC = Red Letters/Clear Panel		
			RM = Red Letters/Mirror Panel		
			RW = Red Letters/White Panel		
			BC = Blue Letters/Clear Panel		
			BM = Blue Letters/Mirror Panel		
			BW = Blue Letters/White Panel		

Notes

¹ Double face available with white or mirror panel only

² Consult factory for alternate legends and custom configurations

VEX-WP-SD Series Wet Location

- Ideal for Wet Location applications in extreme conditions
- UV-stabilized, rugged injection-molded, UL 94 5VA flame-retardant, high temperature polycarbonate housing with impact-resistant, polycarbonate shield
- One piece molded weatherproof silicone gasket

- Ideal for cold locations ranging from -20°C to 50°C (-4°F to 122°F)
- Maintenance-free NiCad battery
- Ceiling, wall or end mount
- 120/277VAC Dual primary, 60Hz input



Download [VEX-WP specification](#) for more information

ORDERING INFORMATION Example: VEX-WP-1-WB-WH-SD01

Series	Style	Power Source	Finish	Legend ¹
GVEX-WP = Green	1 = Single-Face	LB = AC Only	BL = Black	SD01 = 6' Distance
VEX-WP = Red	2 = Double-Face	WB = With Battery	GR = Gray	SD02 = 6' Distance w/Masked Figures
			WH = White	SD03 = 6' Distance Masks Required

Notes ¹ Consult factory for alternate legends and custom configurations