

SPECIFICATIONS

Construction:

The Trace-lite TL802 Series features a heavy duty, die-cast aluminum housing with a paintable textured grey powdercoated finish. The cast aluminum guard screws on to the housing and is secured with a headless set screw. The TL802 is suitable for wet locations and complies with UL Standard 1598 for non-hazardous locations where the luminaire must provide protection for the lamp, socket, and wiring from water, corrosive fumes, non-combustible dusts, non-explosive vapors & gases. The lamp is protected by a heat and impact resistant clear glass globe that is standard, a frosted glass globe can be specified.

Lamps and Ballasts:

The TL802 utilizes a Single universal GX24-q4 compact fluorescent socket with 8" high temperature wire leads, accepts 26, 32 or 42 watt lamps. The TL802 is provided with a high quality electronic programmed start ballast and 120/277VAC input.

Installation:

The TL802 is available in wall mount and ceiling mount. A weatherproof junction box with 3/4" NPT hubs and rugged mounting tabs is included with wall & ceiling styles and includes one (1) 3/4" x 1/2" reducing bushing for those applications that require 1/2" conduit or fittings.

Listing:

The TL802 is suitable for wet locations and complies with UL standard 1598 for non-hazardous locations where the luminaire must provide protection for the lamp, socket, and wiring from water, corrosive fumes, non-combustible dusts, non-explosive vapors & gases.

Warranty:

Any housing component that fails due to manufacturer's defect is guaranteed for two years from time of shipment. Ballasts are warranted for one year from time of shipment. Warranty does not apply to damages caused by improper installation, abuse, fire or acts of God. Lamp is not covered by manufacturer's warranty.

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



TL802-2B

TL802-2W



DIMENSIONS

Mounting	Width	Height *	Depth
CEILING	7 1/8"	15"	7 1/8"
WALL	7 1/8"	18 1/4"	7 7/8"

* Height of wall mount is from the top edge of the wall plate to the bottom of the guard.

ORDERING INFORMATION

Example: TL802-CF-32-120/277-2W

Series	Lamp Type	Lamp Wattage	Input Voltage	Mounting
TL802	CF = Compact Fluorescent	26 = 26 Watts	120/277 = 120/277VAC	2B = Ceiling Mount J-Box with 3/4" hubs
		32 = 32 Watts		2W = Wall Mount J-Box with 3/4" hubs
		42 = 42 Watts		

Specifications are subject to change without notice.
Installation must be performed in accordance with
Barron Lighting Group installation instructions.

10810072 02/17