



For the complete line of specialtyLED[®] products, visit us online at barronltg.com or call 800.533.3948.

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____

XFMR-DIM-XX-20

20W - 12V OR 24V MAGNETIC DIMMABLE LED POWER SUPPLY

FEATURES

- 3 year free replacement warranty
- Fully dimmable with low-voltage magnetic dimmer
- 1/8" thick, power coated steel NEMA 3R case
- Standard with mandatory secondary protection
- Meets Class 2 output limits
- 12 or 24 Volt "DC" rated output
- Meets or exceeds all UL, CUL, ANSI/UL, CSA requirements

CONFORMANCE TO CODES AND STANDARDS

- Meets the requirements for UL standards 2108 and 1838
- Mandatory secondary protection, as stated in the National Electric Code Article 411, (1993, 1996, 1999, 2002, 2005 and 2008)
- Maybe be used with individual Listed components to meet system requirements, as long as all parts are listed to the same ANSI/UL standard




3 YEAR
WARRANTY

ORDERING INFORMATION

Example: XFMR-DIM-12-20

	12 Volt, 20 Watt	24 Volt, 20 Watt
Part Number:	XFMR-DIM-12-20	XFMR-DIM-24-20
Primary Voltage:	120VAC-1A MAX	120VAC-1A MAX
Output Voltage:	12VDC-2A MAX	24VDC-1A MAX
Breakers:	1x2A	1x1A
Frequency:	60 Hz	60 Hz
Dimensions:	8.5" x 3.5" x 3"	8.5" x 3.5" x 3"
Weight:	3 LBS.	3 LBS.

WIRING DIAGRAM



This is a transformer-based power supply. To dim, use a Low Voltage Magnetic Dimmer on the Primary.

Input connection are the White / Black wires with Wire Nuts Attached.

Output is through the White connection block:
Red is Positive / Black is Negative

SPECIFICATIONS ARE SUBJECT
TO CHANGE WITHOUT NOTICE