

DESCRIPTION

6" Downlight white baffle trim with integrated LED light engine in a single compact design that fits most standard 6" recessed housings. Also works in new construction applications (no housing required).

SPECIFICATIONS

Construction:

- Die-cast aluminum housing with white baffle trim
- Flexible cable

Optics/ LEDs:

- Long-life LEDs with up to 54,000 hours at 70% lumen maintenance
- Choice of 3500K (±245), 4000K (±275) or 5000K (±283) color temperatures with 80 CRI
- Produces up to 1700 lumens

Electrical:

- Saves 75% energy compared to incandescent sources
- EN61000-4-5 surge protection (line-neutral, 1kV; line-neutral-ground, 2.5kV)
- Type IC, inherently protected, access above ceiling required
- Power factor ≥ 0.90 with input
- 120V-277VAC, 50/60Hz
- 18 Watts power consumption
- 0-10V Dimming
- Operating temperatures: -20°C to 40°C (-4°F to 104°F)

Installation:

- Compatible with most 6" housings
- Snap-on white baffle trim accessory
- Snap-on silver reflector trim accessory available for field installation
- Flex-cable wires easily into a J-box
- Easy installation in new construction or retrofit applications

Testing & Compliance:

- Tested in accordance with IESNA LM79 & LM80
- UL Listed for Wet Locations
- Passes FCC Class A


Warranty:

- Five year warranty (terms and conditions apply)


Note: Environment and application will affect actual performance. Typical values and 25°C used for testing. Specifications subject to change without notice.

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____

AVAILABLE WHILE SUPPLIES LAST



Baffle/Trim Accessories



Ordering Information Example: BRK-6A-17L-4K

SKUs	Description
BRK-6A-17L-35K	6" Architectural Downlight, 3500K
BRK-6A-17L-4K	6" Architectural Downlight, 4000K
BRK-6A-17L-5K	6" Architectural Downlight, 5000K

Notes:

¹ Order as a separate line item. Shipped in a separate box for final installation in the field.

Accessories¹ (Field Installed)

LED56-TRMPLT-ECO-SQ = White Square Baffle Trim (snap-on)
LED6A-TRMPLT-ECO-SPWHT = Silver & White Round Baffle Trim (snap-on)
LED56-TRMPLT-ECO-BK = Black Round Baffle (snap-on)
LED56-TRMPLT-ECO-N = Nickel/Silver Round Baffle (snap-on)
LED56-TRMPLT-ECO-BZ = Bronze/Moca Round Baffle (snap-on)
BL6CLED-ND = Mounting Frame with J-box
ZZ-BARHANGER-ARCHCAN-FLAT27 = Hanger Bar (2 required)