

**HL SERIES**

# HAZARDOUS LOCATION FIXTURES

**HLC Series**



**EXIT COMBO**

**HLE Series**



**EXIT**

**HLU Series**



**EMERGENCY LIGHT**

**HLR Series**



**REMOTE**

 **EXITRONIX**<sup>®</sup>  
emergency lighting

**RATED FOR CLASS I, DIVISION 2, GROUPS A, B, C & D**

Maintenance-free NiCad battery  
Corrosion-resistant  
Operating temperature  
Optional G2 Self-test/Self-Diagnostics

**THE HL SERIES HAZARDOUS LOCATION FIXTURES** ARE EXPERTLY DESIGNED FOR CHALLENGING ENVIRONMENTS, PROVIDING RELIABLE AND EFFICIENT ILLUMINATION WHERE IT'S NEEDED MOST. BUILT FOR DURABILITY AND SAFETY, THESE FIXTURES ARE **RATED FOR CLASS 1, DIVISION 2, GROUPS A, B, C, & D**, MAKING THEM IDEAL FOR DEMANDING APPLICATIONS.

## KEY FEATURES

- Rated for Class 1, Division 2, Groups A,B,C, & D
- Remote capacity from 4.8W up to 15W (HLC only)
- 3.6W LED lamp heads offering center-to-center spacing up to 47' (HLC, HLU & HLR)
- IP66 Rated, UL Listed for Wet Locations
- Easy snap-out chevron directional indicators (HLC & HLE only)
- California Energy Commission (CEC) compliant
- Maintenance-free NiCad battery
- Corrosion-resistant, fiberglass reinforced polycarbonate housing
- Operating temperature: Down to -20°C to 50°C (-4°F to 122°F)
- Optional G2 Self-test/Self-Diagnostics available



Specifications are subject to change without notice.  
Installation must be performed in accordance with  
Barron Lighting Group installation instructions.

10840532 Rev 1

**BARRON**<sup>®</sup>  
lighting group

7885 North Glen Harbor Blvd  
Glendale, Arizona 85307  
800.533.3948  
barronlg.com