

RGM Series

Medium Glass Refractor LED Wallpack

Delivers up to 4,700lm

DLC Qualified Product

10KVA Surge Protected



RGL Series

Large Glass Refractor LED Wallpack

Delivers over 10,500lm at 100w

DLC Qualified Product

10KVA Surge Protected



RGM | RGL Series

Glass Refractor LED Wallpacks




Trace*Lite's latest generation of glass refractor LED wallpacks feature an updated LED light engine that improves efficacy, lumen output and thermal management while still maintaining the consistency of our proven traditional housing. The RGM and RGL housings are constructed of die-cast aluminum in a dark bronze finish that provides durable protection against environmental conditions, corrosion and the elements. It is UL Listed for Wet Locations. RGM and RGL's light engines are protected by a high-impact borosilicate glass prismatic lens that maximizes light output for general purpose area and security lighting. These versatile luminaires are ideal to match existing or retrofit HID legacy designs.

Key Features

- Die-cast aluminum housing
- Prismatic borosilicate glass refractor
- 10kVA surge protection
- Standard 4000K CCT
- UL Listed for wet location
- 0-10V dimmable driver
- Bronze finish
- Operating temperature: -20°C to 40°C (-4°F to 104°F)
- Mounts to 3" or 4" j-box or 1/2" conduit
- Over 50,000 hrs L70 at 40°C
- DLC Qualified Product


Dimensions

RGM



Weight: 12.8 lbs.

RGL



Weight: 19.6 lbs.

Specs at a Glance

Series	RGM		RGL
Wattage (w)	30	40	100
Lumens (lm)	3,468	4,710	10,515
Efficacy (LPW)	124	118	106
Equivalency	150w HID	250w HID	400w HID
CCT	4000K		
CRI	≥ 71		
Input Voltage	120 - 277VAC, 50/60Hz		
Warranty	5 Years		
Certifications	UL/cUL listed for wet locations, DLC		
Ambient Temp	-20°C to 40°C (-4°F to 104°F)		

Ordering Information

Model	Description	Accessories ¹ (Field Installed)
RGM-30-VS-4K	LED Wallpack, Medium glass refractor, 30w, 120-277VAC, 4000K CCT, Bronze finish	PC1 = 120VAC Photocontrol
RGM-40-VS-4K	LED Wallpack, Medium glass refractor, 40w, 120-277VAC, 4000K CCT, Bronze finish	PC2 = 208-277VAC Photocontrol
RGL-100-VS-4K	LED Wallpack, Large glass refractor, 100w, 120-277VAC, 4000K CCT, Bronze finish	TL-MS-120 = Outdoor PIR sensor, 120VAC, 60Hz TL-MS-277 = Outdoor PIR sensor, 277VAC, 60Hz

Notes

¹ Order as separate line item. Shipped in separate box for final installation in field.

Please visit our website for the latest information.

10840216 05/17

