

DESCRIPTION

The Trace-lite TL205 Series is ideal for outbuildings, arenas, parks, sports fields, sign illumination, and other areas where general floodlighting is necessary.

SPECIFICATIONS

Construction:

The Trace-lite TL205 Series features a durable, corrosion-resistant, die-cast aluminum lamp and ballast enclosure with an architectural bronze powder coated finish. Standard 19" spun aluminum reflector provides 5H x 4V light distribution; four other optional NEMA type reflectors are available. Enclosure is fully sealed and gasketed, and is Wet Location Listed for outdoor use and includes corrosion-resistant hardware. The lamp is protected by a high-impact, heat-resistant tempered glass lens. TL205 is suitable for wet locations.

Lamps & Ballasts

Metal Halide: BT56 type lamp 1500 watts, utilizing a mogul base, glazed porcelain socket pulse rated for 4KV with a CWA ballast rated for a minimum operating temperature of -30°C (-22°F).

Installation:

Angle indicators on adjustable socket make aiming easy. 9/16" mounting bolt is standard, optional mounts are available. Optional pole top mount and large mounting yoke are also available.

Listing:

The TL205 is suitable for wet locations.

Warranty:


Any housing component that fails due to manufacturer's defect is guaranteed for two years from time of shipment. Ballasts, Capacitors, and Ignitors are warranted for one year from time of shipment. Warranty does not apply to damages caused by improper installation, abuse, fire or acts of God. Lamp is not covered by manufacturer's warranty.

Model: _____ Date: _____
Accessories: _____
Job Name: _____ Type: _____




SAMPLE PHOTOMETRICS

TL205-MH-1000 Mounted at 10' with 15° Tilt



DIMENSIONS



Approximate Weight: 25 lbs.
EPA: 2.5

ORDERING INFORMATION

Example: TL205-MH-1500-MT

Series	Lamp Type	Lamp Wattage	Input Voltage	Options (Factory Installed)
TL205	MH = Metal Halide	Metal Halide 1500 = 1500 Watts	MT = 120/208/240/277VAC	T2R ¹ = IES Type 2 Reflector T3R ¹ = IES Type 3 Reflector T45R ¹ = IES Type 4/5 Reflector T6R ¹ = IES Type 6 Reflector
Notes				Accessories² (Field Installed)
¹ Replaces standard reflector				PTM205 = Pole Top Mount
² Order as separate line item				LHY205 = Large Handle Yoke