

SPECIFICATIONS

Construction:

The Trace-lite TL702-CF Series features a durable, extruded aluminum enclosure available in white, black or bronze powder coated finish. Enclosure is fully sealed and gasketed, and is Wet Location Listed for outdoor use. Enclosure and hardware are corrosion resistant. The TL702-CF is available with an adjustable specular aluminum reflector or internal aluminum louvres. The lamps and reflectors are protected by a high-impact, UV stabilized polycarbonate lens.

Lamps & Ballasts

Compact Fluorescent: 42 watt lamp, utilizing either a GX23-2 or GX24-q3 base with a magnetic ballast rated for a minimum operating temperature of -4°C (25°F) or electronic programmed start ballast rated for a minimum operating temperature of -20°C (-4°F).

For pathway illumination, it is recommended to use a 42 watt lamp.

Installation:

The Trace-lite TL702-CF Series features a sturdy base plate anchored with three 8" J-bolts, bollard body is anchored to base using tamper resistant hardware.

Listing:

The TL702-CF is suitable for wet locations.

Warranty:

Any housing component that fails due to manufacturer's defect is guaranteed for two years from time of shipment. Ballasts, Capacitors, and Ignitors are warrantied for one year from time of shipment. Warranty does not apply to damages caused by improper installation, abuse, fire or acts of God. Lamp is not covered by manufacturer's warranty.

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



ORDERING INFORMATION

Example: TL702-CF-42-IL-120/277

Series	Lamp Type	Lamp Wattage ¹	Refractor	Input Voltage	Finish
TL702	CF = Compact Fluorescent	42 = 42 Watts	IL = Internal Louvres	120/277 = 120/277VAC	Blank = Bronze
			IR = Adjustable Reflector		WH = White
Notes					BL = Black

¹ 42 watt lamps are recommended for pathway illumination

² Specify voltage


³ Order as separate line item

Accessories³ (Field Installed)


MK700-8 = Replacement Mounting Kit, Brkt & 8" Anchor Bolts (Inc. Standard)

SAMPLE PHOTOMETRICS


TL702-CF-42-IL INTERNAL LOUVRES



DIMENSIONS



TL702-CF-42-IR INTERNAL REFLECTOR



MOUNTING TEMPLATE

