

The RT1 LED Retrofit Kit reduces exit sign energy consumption up to 97% and eliminates maintenance expense providing a bright, uniform look.

FEATURES

- Up to 97% energy savings
- Direct wire (120 or 277V) or socket ready (120V)
- High-intensity, red, green or white LEDs
- Bright, uniform illumination of exit face
- Consumes only 1.1 watts of power
- Surge-protected, parallel circuitry
- Maintenance-free installation and operation
- Each section measures 6" L x 1" W x 3/4" H
- Assembled in the U.S.A.

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



WARRANTY

Any component that fails due to a manufacturing defect is guaranteed for one year. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Exitronix warranty document for detailed information. (Terms and conditions apply)



ORDERING INFORMATION Example: RT1-A-S-B

Series	Voltage	Connection	Socket Base ²	Accessories ⁴ (Field Installed)
RT1 = Red	A = 120VAC	D = Direct Wire	I = Intermediate Base	RLKIT = Red Diffuser Kit w/Reflector
GRT1 = Green	V = 277VAC	S ¹ = Socket Ready	B = Bayonet Base	GRLKIT ³ = Green Diffuser Kit w/Reflector
WRT1 = White			C = Candelabra Base	
			M = Medium Base	

Notes

- ¹ Not available on 277VAC units
- ² Available on socket ready units only
- ³ GRT1 units supplied standard with green diffuser kits
- ⁴ Order as separate line item