



SCAN QR CODE
FOR PRODUCT DETAILS



EXTRONIX
emergency lighting

barronltg.com

HIGH-ABUSE VANDAL-RESISTANT LED EXIT SIGN

Durable, high abuse steel construction.

Vandal-resistant hardware included.

Available in side, top and wall mount configurations.

Available Self-test/Self-diagnostics and IP65 rated options.

HAE Series

HIGH-ABUSE, VANDAL-RESISTANT LED EXIT

The HAE series features a robust cold rolled or stainless steel enclosure, a polycarbonate lens, and vandal-resistant hardware, ensuring durability in even the toughest applications. It is available in side, wall, or top mounting configurations, with red or green LEDs. Additional options include self-test/self-diagnostics (G2) and an IP65 rating (WL). The HAE series is the perfect solution for providing clear and reliable exit signage in entryways, stairwells, corridors, and other areas within correctional facilities, detention centers, behavioral health centers, public housing, parks, hospitals, or any space requiring a heavy-duty, vandal-resistant EXIT sign.



FEATURES & BENEFITS

- Durable, high-abuse construction, IK10 Rated
- Vandal-resistant hardware
- Available in side, top and wall mount configurations
- Self-test/self-diagnostics (G2) and IP65 (WL) options available
- Top mount is ligature resistant when mounted with pick-proof caulk
- California Energy Commission (CEC) compliant



SPECIFICATIONS

Illumination:	Constant, uniform illumination by long-life, high intensity, red or green LEDs
Housing:	One piece die-formed cold rolled or stainless steel
Input:	120/277V Dual primary, 60Hz input
Battery:	Maintenance-free NiCad battery
Operating Temp:	50°F to 113°F (10°C to 45°C)
Run Time:	90 Minute emergency run time, 24 hour recharge time
Legend:	Fully-illuminated 6" characters with 3/4" stroke, field selectable directional chevrons included for all configurations, includes red and green diffusers
Mounting:	Wall, Top, or Side Mount
Finishes:	Black, White, or Brushed Finish
Options:	Self-Test/Self-Diagnostics (Option: G2) Wet Location Rated, Rated IP65 (Option:WL)
Certifications:	ETL Listed, Salt spray test: 1,000 hours; Reflectance: 92%, IP65 per IEC 60598, meets or exceeds UL 924 and NFPA 101 Standards, meets or exceeds CSA and NRCAN requirements, IK10 Impact Rated



ORDERING INFORMATION (Example: HAE-1-WB-B-14-R-W-TH-BF-G2)

Series	Exit Faces	Power Source	Housing/Door	Gauge Size	Legend Color
HAE	1 = Single-face	LB = AC Only	B = Brushed Stainless Steel	12 ¹ = 12 Gauge	G = Green Letters
	2 = Double-face	WB = NiCad Battery	C = Painted Cold Rolled Steel	14 = 14 Gauge	R = Red Letters
			S = Painted Stainless Steel	16 = 16 Gauge	
				18 = 18 Gauge	

Mouting	Fasteners	Finish	Options	Accessories ⁶ (Field Installed)
S = Side Mount	TH = Torx Head w/Center Pin	BL ⁴ = Black Finish	G2 ⁵ = Self-Test/Self-Diagnostics	TS = Torx Screwdriver
T ² = Top Mount		BF = Brushed Finish	WL = Wet Location (IP65)	
W ³ = Wall Mount		WH ⁴ = White Finish		

Notes

¹ Only available Cold Rolled Steel material

⁴ N/A with brushed housing material

² Top mount is ligature resistant when mounted with pick-proof caulk

⁵ Only available with battery (WB)

³ Wall mount is available in single-face only

⁶ Field installed, order as separate line item