



**EXITRONIX**  
emergency lighting

[barronltg.com](http://barronltg.com)



SCAN QR CODE  
FOR PRODUCT DETAILS



# HIGH-ABUSE, VANDAL & LIGATURE-RESISTANT LED EXIT SIGN

Durable, high-abuse, ligature-resistant steel construction.

Vandal-resistant hardware included.

Wall mount configurations.

Available Self-test/Self-diagnostics and IP65 rated options.

# HALRE Series

## HIGH-ABUSE, VANDAL AND LIGATURE-RESISTANT LED EXIT

The HALRE series features a robust cold rolled or stainless steel enclosure, a polycarbonate lens, and vandal-resistant hardware, ensuring durability in even the toughest applications. It is available in a wall mount configuration, with red or green LEDs. Additional options include self-test/self-diagnostics (G2) and an IP65 rating (WL). The HALRE series is the perfect solution for providing clear and reliable exit signage in entryways, stairwells, corridors, and other areas within correctional facilities, detention centers, behavioral health centers, public housing, parks, hospitals, or any space requiring a heavy-duty, vandal-resistant EXIT sign.



### FEATURES & BENEFITS

- Durable, high-abuse, vandal-resistant construction, IK10 Rated
- Angled design ensures anti-ligature functionality
- Vandal-resistant hardware
- Available in wall mount configurations
- Self-test/self-diagnostics (G2) and IP65 (WL) options available
- California Energy Commission (CEC) compliant



### SPECIFICATIONS

Illumination:	Constant, uniform illumination by long-life, high intensity, red or green LEDs
Housing:	One piece die-formed cold rolled or stainless steel
Input:	120/277V Dual primary, 60Hz input
Battery:	Maintenance-free NiCad battery
Operating Temp:	50°F to 113°F (10°C to 45°C)
Run Time:	ETL Listed 90 Minute emergency run time, 24 hour recharge time
Legend:	Fully-illuminated 6" characters with 3/4" stroke, field selectable directional chevrons included for all configurations, includes red and green diffusers
Mounting:	Wall Mount
Finishes:	Black, White, or Brushed Finish
Options:	Self-Test/Self-Diagnostics (Option: G2) Wet Location Rated, Rated IP65 (Option:WL)
Certifications:	ETL Listed, Salt spray test: 1,000 hours; Reflectance: 92%, IP65 per IEC 60598, meets or exceeds UL 924 and NFPA 101 Standards, meets or exceeds CSA and NRCAN requirements, IK10 Impact Rated

### ORDERING INFORMATION (Example: HALRE-WB-C-14-R-TH-WH-G2)

Series	Power Source	Housing/Door	Gauge Size	Legend Color
HALRE	LB = AC Only	B = Brushed Stainless Steel	12 <sup>1</sup> = 12 Gauge	G = Green Letters
	WB = NiCad Battery	C = Painted Cold Rolled Steel	14 = 14 Gauge	R = Red Letters
		S = Painted Stainless Steel	16 = 16 Gauge	
			18 = 18 Gauge	

Fasteners	Finish	Options	Accessories <sup>5</sup> (Field Installed)
TH = Torx Head w/Center Pin	BL <sup>2</sup> = Black Finish	G2 <sup>3</sup> = Self-Test/Self-Diagnostics	TS = Torx Screwdriver
	BF = Brushed Finish	WL <sup>4</sup> = Wet Location (IP65)	
	WH <sup>2</sup> = White Finish		

#### Notes

<sup>1</sup> Only available Cold Rolled Steel material

<sup>4</sup> Wet Location does not include ligature-resistant listing

<sup>2</sup> N/A with brushed housing material

<sup>5</sup> Field installed, order as separate line item

<sup>3</sup> Only available with battery (WB)