

LED STRIP LIGHTS

WITH BATTERY BACKUP OPTION

Battery backup option provides 800 lumens and 90 minutes of emergency run time.

Uniform illumination in lengths of 2', 4' and 8'.

DLC® PREMIUM maximizes utility rebates.

Easy mounting and linkable.

UP TO **146** LUMENS PER WATT



TRACE LITE
commercial & industrial lighting

barrontg.com

TSL

Linkable LED Strip Light

The TSL Series includes 2', 4' and 8' linkable LED strip lights designed to replace fluorescent strip lighting. The TSL Series delivers general ambient lighting in a variety of indoor settings, including schools, hospitals, stores and is the perfect choice for both new construction and retrofits. This high-efficacy luminaire is a cost-effective solution that provides long-life, uniform illumination and easy installation.



Key Features

- 2', 4' and 8' lengths up to 8000 lumens
- Available in 3500K, 4000K and 5000K CCT
- Uniform illumination along the entire length of the luminaire with no visible LED pixilation
- Ease of installation with snap-on mounting clips and wiring access plate
- Dimming motion sensor accessory with daylight harvesting capability
- Integral UL924 Listed battery pack provides 800 lumens and 90 minutes of run time for path of egress
- Linkable adaptor accessory allows for continued rows up to 240' with seamless illumination
- DLC PREMIUM Qualified maximizes energy savings and utility rebates
- UL Listed for Damp Locations



Specs At A Glance*

Length	2'	4'	8'	
Wattage (W)	20W	24W	32W	64W
Lumens (lm)	2918	3255	4181	7943
Efficacy (LPW)	146	132	132	130
Distribution	General 120°			
CCT	3500K, 4000K, 5000K			
CRI	≥80			
Input Voltage	120-277VAC, 50/60Hz			
Operating Temp	-20°C to 40°C (-4°F to 104°F)			
Certifications	UL Listed for Damp Locations, DLC PREMIUM			
Warranty	5 Years			
Weight	2.5 lbs	4.8 lbs	9 lbs	

*Nominal Wattage. Tested at 5000K CCT

Note: Environment and application will affect actual performance. Typical values and 25°C (77°F) used for testing. Specifications subject to change without notice.

Dimensions

Model	L	W	H
TSL-2	24.0"	3.2"	3.5"
TSL-4	48.0"	3.2"	3.5"
TSL-8	96.0"	3.2"	3.5"

Ordering Information

Example: TSL-4-32-4K-BB

Series	Length/Wattage	CCT	Options	Accessories ² (Field Installed)
TSL	2-20 = 2', 20W	35K = 3500K	BB ¹ = Battery Backup	TL-MSC = Dimming occupancy sensor
	4-24 = 4', 24W	4K = 4000K		TL-MSC-REMOTE = Remote control for TL-MSC
	4-32 = 4', 32W	5K = 5000K		TSL-CHK ³ = 5' Cable + hook kit
	8-64 = 8', 64W			TSL-L4 = Linkable adaptor and wire harness for 4' units
				TSL-L8 = Linkable adaptor and wire harness for 8' units

Notes:

¹ Not compatible with linkable adaptor accessories (TSL-L4, TSL-L8)

² Order as a separate line item; shipped in a separate box for field installation

³ Two kits are required for TSL-8 (8') units



800.533.3948 | barronltg.com

MKT-LIT-TSL 10840297 08/19